

Semi-recessed for discreet look



360° rotation for total flexibility



CRi > 90 providing true colour appearance

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Available with a choice of a matt black or matt white finish

A sleek cylindrical style with hidden fixings

Maximum flexibility with tilt and rotate function to direct light exactly where it is needed

7 year warranty: Collingwood's signature quality you can trust

1901 SPOT

Sleek, low glare, rotatable spot light

FEATURES


IP rating	IP44
CSP Switchable	Dim to Warm
Tiltable	90°
UGR	UGR<16
Dimmable Option	Yes (Mains)
LED Lifetime	L70 70,000h
Colour Rendering Index	CRi>90
Colour Consistency	SDCM3
Emergency Option	Yes
Rotation Angle	355°

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	440g
Insulation Coverable	No
Inrush Current	2.6A/33ms
Cut Out Size	N/A
Construction Material	Aluminium
UK Bathroom Zone	1
Maximum ceiling thickness	40 mm
SELV	Yes
Electric Class (1, 2, 3)	1
Suitable for coastal areas	No
Install Connector Type	Loop in / Loop out
UK Building Regulations	Part P, L, C & E
FR Building Regulations	Satisfait les essais au fil incandescent: 650°C
Dimmer Type	Mains
Power Factor	0.80

PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
BSL15A27NM	Matt white RAL9003	Rotatable Spot Black Baffle Semi-Recessed	9.0W	2700K	15°	800	89	6588	
BSL15A27ND	Matt white RAL9003	Rotatable Spot Black Baffle Semi-Recessed	9.0W	2700K	15°	800	89	6588	
BSL15A27NV	Matt white RAL9003	Rotatable Spot Black Baffle Semi-Recessed	9.0W	2700K	15°	800	89	6588	
BSL15A27MM	Matt white RAL9003	Rotatable Spot Black Baffle Semi-Recessed	9.0W	2700K	24°	800	89	3250	
BSL15A27MD	Matt white RAL9003	Rotatable Spot Black Baffle Semi-Recessed	9.0W	2700K	24°	800	89	3250	
BSL15A27MV	Matt white RAL9003	Rotatable Spot Black Baffle Semi-Recessed	9.0W	2700K	24°	800	89	3250	
BSL15A27WM	Matt white RAL9003	Rotatable Spot Black Baffle Semi-Recessed	9.0W	2700K	50°	800	89	1300	
BSL15A27WD	Matt white RAL9003	Rotatable Spot Black Baffle Semi-Recessed	9.0W	2700K	50°	800	89	1300	
BSL15A27WV	Matt white RAL9003	Rotatable Spot Black Baffle Semi-Recessed	9.0W	2700K	50°	800	89	1300	





More than a century of design and innovation helped inspire the creation of the luxurious architectural 1901 range, for when only the best will do. 1901 is both contemporary and classic, with a focus on premium fittings, a high-quality performance and easy integration into control systems. Perfect for luxury residential and hospitality projects, 1901 showcases an aesthetically simple, low-glare luminaire design, with market-leading technical performance. The detailed fittings come in a variety of stylish options including a choice of bezels, adjustability, colour temperatures, beam angles, dimming methods, and IP ratings to perfectly complete the look of any interior design project. Simply configure your product to find the relevant product code. The range is engineered to be as easy to use as possible and can fit seamlessly into the installation and commissioning stages of a lighting project.

BSL15A30NM	Matt white RAL9003	Rotatable Spot Black Baffle Semi-Recessed	9.0W	3000K	15°	800	89	7137	
-------------------	-----------------------	---	------	-------	-----	-----	----	------	--

WIRING INFORMATION

Cable / Flying Lead	2 x twin & earth (6242Y 3x1.5mm) or 3-core cable (R02V 3x1.5mm)
Cable Required for Connector	2 x twin & earth (6242Y 3x1.5mm) or 3-core cable (R02V 3x1.5mm)
Type of Wiring Required	Parallel

ACCESSORIES

LEDEP10	3hr non-maintained, self-test emergency pack (plug&br/>& play)	Sold Separately
----------------	--	-----------------