



Semi-recessed for discreet look



360° rotation for total flexibility



CRI 90 providing true colour appearance

1901 Spot

Sleek, low glare, rotatable spot light

Features

| | |
|------------------------|-------------|
| IP rating | IP44 |
| CSP Switchable | Dim to Warm |
| Tiltable | 90° |
| UGR | 14 |
| Dimmable Option | Yes (Mains) |
| LED Lifetime | L70 70,000h |
| Colour Rendering Index | CRI>90 |
| Colour Consistency | SDCM3 |
| Emergency Option | Yes |
| Rotation Angle | 355° |

Installation Information

| | |
|-----------------------------|---|
| Input | 220-240V AC |
| Maximum Ambient Temperature | 40°C |
| Weight | 440g |
| Insulation Coverable | No |
| Inrush Current | 2.6A/33ms |
| Construction Material | Aluminium |
| UK Bathroom Zone | 1 |
| SELV | SELV |
| Electric Class (1, 2, 3) | 2 |
| Suitable for coastal areas | No |
| Install Connector Type | Loop in / Loop out |
| UK Building Regulations | Part P, L, C & E |
| FR Building Regulations | Satisfait les essais au fil incandescent: 650°C |
| Dimmer Type | Mains |
| Power Factor | 0.8 |

Guarantee


Warranty 7 years

Features & benefits

- Available with a choice of a matt black or matt white finish
- A sleek cylindrical style with hidden fixings
- Maximum flexibility with tilt and rotate function to direct light exactly where it is needed
- 7 year warranty: Collingwood's signature quality you can trust

Photometrics @ 25°C

| Product Code | Finish | Type | W | Colour | Beam | lm | lm/W | Lx @ 1m | Energy |
|--------------|-----------------------|---|------|--------|------|-----|------|---------|--------|
| BSL15A27NM | Matt white RAL9003 | Rotatable Spot Black Baffle Semi- Recessed | 9.6W | 2700K | 12° | 600 | 63 | 6588 | |
| BSL15A27ND | Matt white RAL9003 | Rotatable Spot Black Baffle Semi- Recessed | 9.6W | 2700K | 12° | 600 | 63 | 6588 | |
| BSL15A27NV | Matt white RAL9003 | Rotatable Spot Black Baffle Semi- Recessed | 9.6W | 2700K | 12° | 600 | 63 | 6588 | |
| BSL15A27MM | Matt white RAL9003 | Rotatable Spot Black Baffle Semi- Recessed | 9.6W | 2700K | 24° | 590 | 61 | 2866 | |
| BSL15A27MD | Matt white RAL9003 | Rotatable Spot Black Baffle Semi- Recessed | 9.6W | 2700K | 24° | 590 | 61 | 2866 | |
| BSL15A27MV | Matt white RAL9003 | Rotatable Spot Black Baffle Semi- Recessed | 9.6W | 2700K | 24° | 590 | 61 | 2866 | |
| BSL15A27WM | Matt white RAL9003 | Rotatable Spot Black Baffle Semi- Recessed | 9.6W | 2700K | 50° | 575 | 60 | 998 | |
| BSL15A27WD | Matt white | Rotatable | 9.6W | 2700K | 50° | 575 | 60 | 998 | |





collingwood

More than a century of design and innovation helped inspire the creation of the luxurious architectural 1901 range, for when only the best will do. 1901 is both contemporary and classic, with a focus on premium fittings, a high-quality performance and easy integration into control systems. Perfect for luxury residential and hospitality projects, 1901 showcases an aesthetically simple, low-glare luminaire design, with market-leading technical performance. The detailed fittings come in a variety of stylish options including a choice of bezels, adjustability, colour temperatures, beam angles, dimming methods, and IP ratings to perfectly complete the look of any interior design project. Simply configure your product to find the relevant product code. The range is engineered to be as easy to use as possible and can fit seamlessly into the installation and commissioning stages of a lighting project.

| | | | | | | | | | | |
|------------|-----------------------|---|------|-------|-----|-----|----|------|--|--|
| | RAL9003 | Spot Black Baffle Semi- Recessed | | | | | | | | |
| BSL15A27WV | Matt white RAL9003 | Rotatable Spot Black Baffle Semi- Recessed | 9.6W | 2700K | 50° | 575 | 60 | 998 | | |
| BSL15A30NM | Matt white RAL9003 | Rotatable Spot Black Baffle Semi- Recessed | 9.6W | 3000K | 12° | 650 | 68 | 7137 | | |

Wiring Information

| | |
|------------------------------|---|
| Cable / Flying Lead | 2 x twin & earth (6242Y 3x1.5mm ²) or 3-core cable (R02V 3x1.5mm ²) |
| Cable Required for Connector | 2 x twin & earth (6242Y 3x1.5mm ²) or 3-core cable (R02V 3x1.5mm ²) |
| Type of Wiring Required | Parallel |

LED Driver

| Input | Dimming |
|----------|---------|
| 220-240V | Yes |

Accessories

| | | |
|---------|--|-----------------|
| LEDEPI0 | 3hr non-maintained, self-test emergency pack (plug & play) | Sold Separately |
|---------|--|-----------------|