



# 1901 SPOT

Sleek, low glare, rotatable spot light

## FEATURES

IP rating	IP44
CSP Switchable	Dim to Warm
Tilttable	90°
UGR	UGR<16
Dimmable Option	Yes (Mains)
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>90
Colour Consistency	SDCM3
Emergency Option	Yes
Rotation Angle	355°

## INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	440g
Insulation Coverable	No
Inrush Current	2.6A/33ms
Cut Out Size	N/A
Construction Material	Aluminium
UK Bathroom Zone	1
Maximum ceiling thickness	40 mm
SELV	Yes
Electric Class (1, 2, 3)	1
Suitable for coastal areas	No
Install Connector Type	Loop in / Loop out
UK Building Regulations	Part P, L, C & E
FR Building Regulations	Satisfait les essais au fil incandescent: 650°C
Dimmer Type	Mains
Power Factor	0.80

## WIRING INFORMATION

Cable / Flying Lead	2 x twin & earth (6242Y 3x1.5mm) or 3-core cable (R02V 3x1.5mm)
Cable Required for Connector	2 x twin & earth (6242Y 3x1.5mm) or 3-core cable (R02V 3x1.5mm)
Type of Wiring Required	Parallel

## ACCESSORIES

LEDEP10	3hr non-maintained, self-test emergency pack (plug & play)	Sold Separately
---------	--	-----------------



COLLINGWOOD  
LIGHTING

LIGHTING INNOVATION

Semi-recessed for discreet look



360° rotation for total flexibility



CRI 90 providing true colour appearance

## WARRANTY

Warranty 7 years

## FEATURES & BENEFITS

Available with a choice of a matt black or matt white finish

A sleek cylindrical style with hidden fixings

Maximum flexibility with tilt and rotate function to direct light exactly where it is needed

7 year warranty: Collingwood's signature quality you can trust

