



## AUREA 3 TP

Pendant light for accent lighting

### FEATURES

IP rating	IP20
CSP Switchable	Switchable CCT
Tilttable	No
Dimmable Option	Yes
LED Lifetime	L80 50,000h
Colour Rendering Index	CRI>90
Colour Consistency	SDCM3
Rotation Angle	No

### INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 45°C
Weight	620g
Inrush Current	1.6A 37ms
Construction Material	Aluminium
Electric Class (1, 2, 3)	1
Suitable for coastal areas	No
UK Building Regulations	Part P & L
Mounting Options	On Track

### PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Energy
TR43405	White	6W	2700K / 3000K / 4000K	38°	500-550	83-92	A+ F
TR43430	Black	6W	2700K / 3000K / 4000K	38°	500-550	83-92	A+ F

### WIRING INFORMATION

Cable Required for Connector	N/A
Type of Wiring Required	Parallel

### ACCESSORIES

C051710	3-Circuit Aurea Pendant Champagne Sleeve Cover	Sold Separately
C051777	3-Circuit Aurea Pendant Rose Sleeve Cover	Sold Separately
	Track range and accessories	Sold Separately



Colour switchable between  
2700K 3000K and 4000K



IP20 for use internally



CRI 90 providing true colour  
appearance

### WARRANTY

Warranty

5 years

### FEATURES & BENEFITS

A medium beam angle of 38° for a more  
focused light

Long lifetime of 50,000hrs

For use with 3 Circuit Track

