



AUREA 3 T

Spotlight for accent lighting

Features

IP rating	IP20
CSP Switchable	Switchable CCT
Tilttable	90°
Dimmable Option	Yes
LED Lifetime	L80 50,000h
Colour Rendering Index	CRI>90
Colour Consistency	SDCM3
Rotation Angle	350°

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 45°C
Weight	410g
Inrush Current	1.6A 37ms
Construction Material	Aluminium
Electric Class (1, 2, 3)	1
Suitable for coastal areas	No
UK Building Regulations	Part P & L
Mounting Options	On Track

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Energy
TR43330	White	6W	2700K / 3000K / 4000K	38°	500-550	83-92	
TR43305	Black	6W	2700K / 3000K / 4000K	38°	500-550	83-92	

Wiring Information

Cable Required for Connector	N/A
Type of Wiring Required	Parallel

Accessories

C051710	3-Circuit Aurea Spot Champagne Sleeve Cover	Sold Separately
C051777	3-Circuit Aurea Spot Rose Sleeve Cover	Sold Separately
	Track range and accessories	Sold Separately

C
collingwood



Colour switchable between 2700K
3000K and 4000K



IP20 for use internally



CRI 90 providing true colour
appearance

Guarantee

Warranty 5 years

Features & benefits

- A medium beam angle of 38° for a more focused light
- Long lifetime of 50,000hrs
- For use with 3 Circuit Track

