



AUREA 3 T

Spotlight for accent lighting

FEATURES

IP rating	IP20
CSP Switchable	Switchable CCT
Tilttable (°)	90
UGR	UGR<21
Dimmable Option	Yes
LED Lifetime	L80 50,000h
Colour Rendering Index	CRI>90
Colour Consistency	SDCM3
Rotation angle (°)	350

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 45°C
Weight	410g
Inrush Current	1.6A 37ms
Construction Material	Aluminium
Electric Class (1, 2, 3)	I
Suitable for coastal areas	No
UK Building Regulations	Part P & L
Mounting Options	On Track

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Energy
TR43330	White	6W	2700K / 3000K / 4000K	38°	500-550	83-92	A+ F
TR43305	Black	6W	2700K / 3000K / 4000K	38°	500-550	83-92	A+ F

WIRING INFORMATION

Cable Required for Connector	N/A
Type of Wiring Required	Parallel

ACCESSORIES

C051710	3-Circuit Aurea Spot Champagne Sleeve Cover	Sold Separately
C051777	3-Circuit Aurea Spot Rose Sleeve Cover	Sold Separately
	Track range and accessories	Sold Separately



Colour switchable between
2700K 3000K and 4000K



IP20 for use internally



CRI 90 providing true colour
appearance

WARRANTY

Warranty

5 years

FEATURES & BENEFITS

A medium beam angle of 38° for a more
focused light

Long lifetime of 50,000hrs

For use with 3 Circuit Track

