



Colour switchable between  
2700K 3000K and 4000K



IP20 for use internally



CRI 90 providing true colour  
appearance

## AUREA 3 T

Spotlight for accent lighting

### FEATURES

IP rating	IP20
CSP Switchable	Switchable CCT
Tilttable (°)	90
UGR	UGR<21
Dimmable Option	Yes
LED Lifetime	L80 50,000h
Colour Rendering Index	CRI>90
Colour Consistency	SDCM3
Rotation angle (°)	350

### INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 45°C
Weight	410g
Inrush Current	1.6A 37ms
Construction Material	Aluminium
Electric Class (1, 2, 3)	I
Suitable for coastal areas	No
UK Building Regulations	Part P & L
Mounting Options	On Track

### PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Energy
TR43330	White	6W	2700K / 3000K / 4000K	38°	500-550	83-92	A+ F
TR43305	Black	6W	2700K / 3000K / 4000K	38°	500-550	83-92	A+ F

### WIRING INFORMATION

Cable Required for Connector	N/A
Type of Wiring Required	Parallel

### ACCESSORIES

C051710	3-Circuit Aurea Spot Champagne Sleeve Cover	Sold Separately
C051777	3-Circuit Aurea Spot Rose Sleeve Cover	Sold Separately
	Track range and accessories	Sold Separately

### WARRANTY

Warranty

5 years

### FEATURES & BENEFITS

A medium beam angle of 38° for a more  
focused light

Long lifetime of 50,000hrs

For use with 3 Circuit Track

