



3 Circuit Track



Champagne
C051710

Rose
C051777



Colour switchable between 2700K 3000K and 4000K



IP20 for use internally



CRI 90 providing true colour appearance

AUREA 3 T

Spotlight for accent lighting

FEATURES

| | |
|------------------------|----------------|
| IP rating | IP20 |
| CSP Switchable | Switchable CCT |
| Tilttable (°) | 90 |
| UGR | UGR<21 |
| Dimmable Option | Yes |
| LED Lifetime | L80 50,000h |
| Colour Rendering Index | CRI>90 |
| Colour Consistency | SDCM3 |
| Rotation angle (°) | 350 |

INSTALLATION INFORMATION

| | |
|-----------------------------|--------------|
| Input | 220-240V AC |
| Maximum Ambient Temperature | -20°C - 45°C |
| Weight | 410g |
| Inrush Current | 1.6A 37ms |
| Construction Material | Aluminium |
| Electric Class (1, 2, 3) | I |
| Suitable for coastal areas | No |
| UK Building Regulations | Part P & L |
| Mounting Options | On Track |

WARRANTY

Warranty

5 years

FEATURES & BENEFITS

A medium beam angle of 38° for a more focused light

Long lifetime of 50,000hrs

For use with 3 Circuit Track

PHOTOMETRICS @ 25°C

| Product code | Finish | W | Colour | Beam | lm | lm/W | Energy |
|--------------|--------|----|-----------------------------|------|---------|-------|--------|
| TR43330 | White | 6W | 2700K / 3000K / 4000K | 38° | 500-550 | 83-92 | A F |
| TR43305 | Black | 6W | 2700K / 3000K / 4000K | 38° | 500-550 | 83-92 | A F |

WIRING INFORMATION

| | |
|------------------------------|----------|
| Cable Required for Connector | N/A |
| Type of Wiring Required | Parallel |

ACCESSORIES

| | | |
|---------|---|-----------------|
| C051710 | 3-Circuit Aurea Spot Champagne Sleeve Cover | Sold Separately |
| C051777 | 3-Circuit Aurea Spot Rose Sleeve Cover | Sold Separately |
| | Track range and accessories | Sold Separately |

