





AUREA 3 T

Spotlight for accent lighting

FEATURES

IP rating	IP20	
CSP Switchable	Switchable CCT	
Tiltable	90°	
Dimmable Option	Yes	
LED Lifetime	L80 50,000h	
Colour Rendering Index	CRI>90	
Colour Consistency	SDCM3	
Rotation Angle	350°	

INSTALLATION INFORMATION

Input	220-240V AC	
Maximum Ambient Temperature	-20°C - 45°C	
Weight	410g	
Inrush Current	1.6A 37⊠s	
Construction Material	Aluminium	
Electric Class (1, 2, 3)	1	
Suitable for coastal areas	No	
UK Building Regulations	Part P & L	
Mounting Options	On Track	

PHOTOMETRICS @ 25°C

Product code	Finish	w	Colour	Beam	lm	lm/W	Energy
TR43330	White	6W	2700K / 3000K / 4000K	38°	500-550	83-92	Å F
TR43305	Black	6W	2700K / 3000K / 4000K	38°	500-550	83-92	A F

WIRING INFORMATION

Cable Required for Connector	N/A
Type of Wiring Required	Parallel

ACCESSORIES

CO51710	3-Circuit Aurea Spot Champagne Sleeve Cover	Sold Separately
CO51777	3-Circuit Aurea Spot Rose Sleeve Cover	Sold Separately
	Track range and accessories	Sold Separately



LIGHTING INNOVATION



Colour switchable between 2700K 3000K and 4000K



IP20 for use internally



CRI 90 providing true colour appearance

WARRANTY

FEATURES & BENEFITS

A medium beam angle of 38° for a more

