









CCT Colour Switchable

FEATURES

IP rating	IP65
IK rating	IK08
CSP Switchable	Switchable CCT
Sensor Option	PIR with accessory
Dimmable Option	No
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4
Emergency Option	Yes, Self-Test

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 35°C
Weight	1.20Kg (EM: 1.60Kg)
Inrush Current	30A 0.3ms
Construction Material	Anti-UV Polycarbonate
SELV	Yes
Electric Class (1, 2, 3)	1
Suitable for coastal areas	Yes (with modification)
Install Connector Type	Loop in / Loop out
UK Building Regulations	Part P
Mounting Options	Surface
Power Factor	0.9

Photometrics @ 25°C

Product Code	Finish	Туре	Beam	w	Colour	lm	lm/W	lx@1m	EM lm	Energy
				3000K	2300	115	551	-		
AC4SN	Grey RAL7005	Standard	120°	20W	4000K	2600	130	623	-	A D
			6500K	2500	125	599	-			

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable Required for Connector	H05RN-F cable diameter 4 - 10mm, max conductor size 3x 1.5mm²
Type of Wiring Required	Parallel

ACCESSORIES

	EMBOLTMOPEN	Sold Separately
EMBOLTMCOR	3 hour emergency conversion pack, corridor area, manual test	Sold Separately
PIRBOLT	PIR on/off daylight Sensor	Sold Separately



LIGHTING INNOVATION



CCT switchable between 3000K, 4000K & 6500K



Grade 316 Coastal protection kit available



BESA mounting kit available

WARRANTY

Warranty 5 year
Battery Warranty 2 year
On-Site Warranty 2 year

FEATURES & BENEFITS

IP65 for the highest level of dust protection and able to withstand jets of water from any direction

304 stainless steel clips for high corrosion resistance and anti-tamper screws for vanda proofing

IK08 for robust impact protection

Unique gear tray slots that allow us to easily integrate third party control gear for your project. Just ask.

Extended mounting sliders to help make refurbishment easier

Safety tether cable to gear tray enables fast

Compression cable gland included in fixings kit

Emergency option available



