### High bay specification sheet









# **AREA BAY 150W**

150W High bay luminaire (Replaces 250W or 4X49W T5)

Features	
IP rating	IP65
IK rating	IK10
CSP Switchable	Single CCT
Sensor Option	PIR, Microwave & Daylight
Sensor Option	with accessories
Dimmable Option	Yes (0-10V, PWM and DALI-
Dillillable Option	2)
LED Lifetime	L80 54,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5
<b>Emergency Option</b>	Yes

# **Installation Information**

Input	220-240V AC
Maximum Ambient Temperature	-40°C - 50°C
Weight	2.28kg
Inrush Current	130A 0.63ms
Construction Material	ADC12 ALU alloy, PC front
Construction Material	lens, SS304 Eyelet.
Electric Class (1, 2, 3)	1
Install Connector Type	Flying lead
UK Building Regulations	Part P
UK Protection	Surge Protection 6KV
Mounting Options	Jack Chain, Surface Bracket
Mounting Options	or Rod Mount
Power Factor	0.9

### Photometrics @ 25°C

Product Code	Finish	Туре	w	Colour	Beam	lm	lm/W	EM lm	Energy
HBA2V	Matt black RAL9017	Standard	150W	4000K	110°	24000	160	-	A C
HBA2VEM	Matt black RAL9017	Emergency	150W	4000K	110°	24000	160	650	A C
HBA2D	Matt black RAL9017	DALI-2	150W	4000K	110°	24000	160	-	A C

## **Wiring Information**

_	
Cable / Flying Lead	1.5m H05RN-F 3x1.0mm <sup>2</sup> Ø7mm
Type of Wiring Required	Parallel

### Accessories

Accessories		
HBPIRDLD	Area Bay PIR + Daylight Harvest Sensor	Sold Separately
HBPIR	Area Bay PIR/Daylight Sensor	Sold Separately
HBMWS	Area Bay Microwave/Daylight Sensor	Sold Separately
HBDLS	Area Bay Daylight Sensor	Sold Separately
HBREM	Area Bay Remote Control	Sold Separately
HBBRA	HB Bracket Mount for Standard Luminaire	Sold Separately
HBBRAEXT	HB Extended Bracket Mount for Standard Luminaire	Sold Separately

# collingwood



High efficacy of 160lm/W



Very light weight for easy installation



Emergency option available

### Guarantee

Warranty 5 years Battery Warranty 2 years

### Features & benefits

- High performance dedicated lens for each LED provides efficient optical control
- Choice of PIR, microwave, daylight and wireless control options saves energy and takes just seconds to fit, just plug-in to the centre of the high bay
- Compact and lightweight, our product can be held in one hand and installed by  $\boldsymbol{\alpha}$ single person
- Quick access to LiFePO4 battery compartment for simple replacement
- Removeable driver for easy maintenance
- Impact and corrosion resistant aluminium housing which is 100% recyclable



