

AREA BAY 200W

200W High bay luminaire (Replaces 400W or 4x80W T5)

FEATURES

IP rating	IP65
IK rating	IK10
CSP Switchable	Single CCT
Sensor Option	PIR, Microwave & Daylight
	with accessories
Dimmable Option	Yes (0-10V, PWM and DALI-2)
LED Lifetime	L80 54,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5
Emergency Option	Yes, Manual-Test

INSTALLATION INFORMATION

UNREMOTEMWS

HBPIR

HBMWS

Input	220-240V AC
Maximum Ambient Temperature	Non EM: -20°C - +40°C EM: 0°C - +40°C
Weight	2.00kg
Inrush Current	130A 0.63ms
Construction Material	ADC12 ALU alloy, PC front lens, SS304 Eyelet.
Electric Class (1, 2, 3)	
Install Connector Type	Flying lead
UK Building Regulations	Part P
Mounting Options	Jack Chain, Surface Bracket or Rod Mount
Power Factor	0.9

PHOTOMETRICS @ 25°C

Product code	Finish	Туре	w	Colour	Beam	lm	lm/W	EM lm	Energy
HBA3V	Matt black RAL9017	Standard	200W	4000K	110°	32000	160	-	A C
HBA3VEM	Matt black RAL9017	Emergency	200W	4000K	110°	32000	160	650	A C
HBA3D	Matt black RAL9017	DALI-2	200W	4000K	110°	32000	160	-	A C

WIRING INFORMATION

Cable / Flying Lead	1.5m H05RN-F 3x1.0mm² Ø7mm	
Type of Wiring Required	Parallel	
ACCESSORIES		
HBPIRDLD	Area Bay PIR + Daylight Harvest Sensor	Sold Separately
HBPIR	Area Bay PIR/Daylight Sensor	Sold Separately
HBMWS	Area Bay Microwave/Daylight Sensor	Sold Separately
HBDLS	Area Bay Daylight Sensor	Sold Separately
UNREMOTEMWS	Remote control for use with microwave sensor	Sold Separately
CASZHAGAMB	Casambi Wireless Zhaga PIR+DL Sensor Black 12m (0-10V only)	Sold Separately
CASZHAGASB	Casambi Wireless Zhaga Node Black 12m (0-10V only)	Sold Separately



LIGHTING INNOVATION




Ő

EM!

____ Cł High efficacy of 160lm/W

Very light weight for easy installation



ars

WARRANTY

Warranty	5 y
Battery Warranty	2 y
On-Site Warranty	2 y

FEATURES & BENEFITS

gh performance dedicated lens for each LED
ovides efficient optical control
noice of PIR, microwave, daylight and wireless
ntrol options saves energy and takes just
conds to fit, just plug-in to the centre of the
gh bay
ompact and lightweight, our product can be
ld in one hand and installed by a single
erson
uick access to LiFePO4 battery compartment
r simple replacement
moveable driver for easy maintenance

Removeable driver for easy maintenance

housing which is 100% recyclable

Ø285mm Ø286mm Standard Ø286mm Emergency

01604 495 151 sales@collingwoodgroup.com collingwoodlighting.com