



-  IP20 perfect for internal applications
-  DALI dimmable option available
-  CRI 80 providing true colour appearance

ALLY 3 RDX

Adjustable round recessed spotlight

Features

IP rating	IP20
IK rating	IK02
CSP Switchable	Single CCT
Tilttable	45°
UGR	UGR<19, UGR<22
Dimmable Option	Yes
LED Lifetime	L80 50,000h
Colour Rendering Index	CRI>90
Colour Consistency	SDCM3
Emergency Option	No
Rotation Angle	355°

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-30°C - 50°C
Weight	0.354
Insulation Coverable	No
Inrush Current	N/A
Cut Out Size	105
Construction Material	Aluminium
UK Bathroom Zone	N/A
SELV	Yes
Electric Class (1, 2, 3)	2
Suitable for coastal areas	No
Part B Fire Rating	No



Guarantee

Warranty 5 years

Features & benefits

- Recessed ceiling mounting only
- Quick and easy installation with springs

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Energy
DO529WW05	Black	10W	3000K	38°	1025	72	
DO529WW30	White	10W	3000K	38°	1025	72	

Wiring Information

Cable / Flying Lead	0.5-1.5mm ²
Type of Wiring Required	Parallel

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (intergrated driver)	220-240V	Yes	Yes	N/A

Accessories

CD123	Dimmable DALI constant current converter	Sold Separately
-------	--	-----------------

