

IP20 IP20 perfect for internal applications

DIM DALI dimmable option available

CRI>80 CRI 80 providing true colour appearance

WARRANTY


Warranty

5 years

FEATURES & BENEFITS

Recessed ceiling mounting only

Quick and easy installation with springs



ALLY 4 RDX

Adjustable round recessed spotlight

FEATURES

IP rating	IP20
IK rating	IK02
CSP Switchable	Single CCT
Tiltable (°)	45
UGR	UGR<19
Dimmable Option	Yes
LED Lifetime	L80 50,000h
Colour Rendering Index	CRI>90
Colour Consistency	SDCM3
Emergency Option	No
Rotation angle (°)	355

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-30°C - 50°C
Weight	0.496
Insulation Coverable	No
Inrush Current	N/A
Cut Out Size	128
Construction Material	Aluminium
UK Bathroom Zone	N/A
SELV	Yes
Electric Class (1, 2, 3)	II
Suitable for coastal areas	No
Mounting Options	Recessed
Part B Fire Rating	No

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Energy
DO530WW05	Black	14W	3000K	38°	1270	66	
DO530WW30	White	14W	3000K	38°	1270	66	

WIRING INFORMATION

Cable / Flying Lead	0.5-1.5mm ²
Type of Wiring Required	Parallel

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (intergrated driver)	220-240V	Yes	Yes	N/A

ACCESSORIES

CD140	Dimmable DALI constant current converter	Sold Separately
-------	--	-----------------

38°

