



CCT switchable between 2700K & 3000K (default)



Wattage Switchable between 6,8,10,12, & 15W



Integral photocell as standard

ARC PRO CSP

0% ULOR Wallpack suitable for mounting heights from 2.5 up to 4 metres

FEATURES

IP rating	IP66
IK rating	IK10
CSP Switchable	Switchable CCT
Sensor Option	PC Dusk to Dawn
Dimmable Option	No
LED Lifetime	L70 54,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4
Emergency Option	Yes, Manual-Test
Walk Over / Drive Over	No

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-30°C - 50°C
Weight	2.6kg
Inrush Current	23A
Construction Material	Double powder coated ADC12 aluminium alloy, uv-resistant polycarbonate lens, stainless steel 316 screws
UK Bathroom Zone	2
Electric Class (1, 2, 3)	I
Earth Leakage	N/A
Suitable for coastal areas	Yes
Install Connector Type	Push-fit terminal, loop-in/loop-out
Mounting Options	Wall

WARRANTY

Warranty

5 years

FEATURES & BENEFITS

Custom Optical lens design providing excellent forward throw

0% ULOR (Upward Light Output Ratio) for avoid light pollution

Suitable for coast - C5-M corrosion classification (ISO 9223 : 2012)

Designed to illuminate a pathway efficiently and safely, whilst preserving the habitat

Integral photocell to switch the light ON at dusk and OFF at dawn

Removeable backplate to aid fast installation

Lumen output in emergency mode is 300lm for both 2700K & 3000K

Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	Energy					
ARPBIN	Matt Black RAL9005	Standard	140° x 70°	6W	2700K	850	142	A t t e n t i o n D					
					3000K	850	142						
				8W	2700K	1100	138						
					3000K	1100	138						
				10W	2700K	1400	127						
					3000K	1400	127						
				12W	2700K	1650	138						
					3000K	1650	138						
				15W	2700K	2000	133						
					3000K	2000	133						
				ARPB1NE	Matt Black RAL9005	Emergency	140° x 70°		6W	2700K	850	142	A t t e n t i o n D
										3000K	850	142	
8W	2700K	1100	138										
	3000K	1100	138										
10W	2700K	1400	127										
	3000K	1400	127										
12W	2700K	1650	138										
	3000K	1650	138										
15W	2700K	2000	133										
	3000K	2000	133										

140° x 70°

293mm

97mm

292mm



Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	No flying leads are required; a loop-in, loop-out terminal is supplied.
Type of Wiring Required	Parallel



COLLINGWOOD
LIGHTING

LIGHTING INNOVATION