



Astra



Energy efficient up to 111lm/W



UGR19 for low glare



Quick and easy installation without opening the luminaire

Features

IP rating	IP40
IK rating	IK06
CSP Switchable	Single CCT
UGR	19
Sensor Option	On Request
Dimmable Option	No
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5
Emergency Option	Yes, remotely using Salvus Route

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 50°C
Weight	3.8kg
Inrush Current	12A 0.112ms
Construction Material	Aluminium housing, Microprism lens
Electric Class (1, 2, 3)	2
Install Connector Type	Push-fit terminals 0,5 - 1,5mm ²
Power Factor	0.95

Guarantee

Warranty 5 years

Features & benefits

- Classic shape luminaire with timeless design
- Floating impression when surface mounted
- Minimalist pendant is versatile to suit the decor of any room
- Wall mounted creates interest
- Versatile solution for multiple different applications

Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	Energy
ASW451N40	White RAL9003	450mm	18	4000K	90°	2000	111	
ASW452N40	White RAL9003	450mm	26	4000K	90°	2600	100	

Wiring Information

Cable / Flying Lead	0.75-2.5mm ²
Type of Wiring Required	Parallel

Accessories

ASWSUS2M	Astra Pendant Kit White, 2 metres, 3 core cable	Sold Separately
EMRWMAN	Salvus Route White, Manual Test, Open Corridor Lens	Sold Separately
EMRWST	Salvus Route White, Self Test, Open Corridor Lens	Sold Separately

