



ASTRA

Classic shape luminaire that can be suspended, surface or wall mounted

FEATURES

IP rating	IP40
IK rating	IK06
CSP Switchable	Single CCT
UGR	UGR<19
Sensor Option	No
Dimmable Option	No
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5
Emergency Option	Yes, Self-Test

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 50°C
Weight	3.4kg
Inrush Current	STD: 12A 0.112ms EM: TBC
Construction Material	Aluminium housing, Microprism lens
Electric Class (1, 2, 3)	II
Install Connector Type	Push-fit terminals 0,5 - 1,5mm²
UK Building Regulations	Part P & L
Mounting Options	Ceiling & suspended
Power Factor	0.95

PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	lm/W	EM lm	Energy
ASW451N40	White RAL9003	Standard	18W	4000K	90°	2000	111		
ASW452N40	White RAL9003	Standard	26W	4000K	90°	2600	100		
ASW451N40ES	White RAL9003	Emergency	18W	4000K	90°	2000	111	250	
ASW452N40ES	White RAL9003	Emergency	26W	4000K	90°	2600	100	250	




Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	0.75-2.5mm²
Type of Wiring Required	Parallel

ACCESSORIES

ASWSUS2M	Astra Pendant Kit White, 2 metres, 3 core cable	Sold Separately
EMRWMAN	Salvus Route White, Manual Test, Open Corridor Lens	Sold Separately
EMRWST	Salvus Route White, Self Test, Open Corridor Lens	Sold Separately

-  Energy efficient up to 111lm/W
-  UGR19 for low glare
-  Quick and easy installation without opening the luminaire

WARRANTY

Warranty	5 years
On-Site Warranty	2 years

FEATURES & BENEFITS

- Classic shape luminaire with timeless design
- Floating impression when surface mounted
- Minimalist pendant is versatile to suit the decor of any room
- Wall mounted creates interest
- Versatile solution for multiple different applications
- Integral emergency option (for wall mount application only)

