

1901 DOWNLIGHT

Design your light! Modular Architectural Downlight Range

FEATURES

IP rating CSP Switchable Tiltable (°) UGR Dimmable Option LED Lifetime Colour Rendering Index Colour Consistency Emergency Option Rotation angle (°)

IP65
Single CCT
Fixed
UGR<19
Yes (1-10V)
L70 70,000h
CRI>90
SDCM3
Yes, using converter
Fixed

INSTALLATION INFORMATION

Input	220-240V AC				
Maximum Ambient Temperature	40°C				
Weight	240g				
Insulation Coverable	No				
Inrush Current	10A/22⊠s				
Cut Out Size	65-68				
Construction Material	Aluminium				
UK Bathroom Zone	1				
Maximum ceiling thickness	40 mm				
SELV	Yes				
Electric Class (1, 2, 3)	II				
Suitable for coastal areas	No				
Install Connector Type	Loop in / Loop out				
UK Building Regulations	Part P, L & B				
FR Building Regulations	Satisfait les essais au fil				
FR building Regulations	incandescent: 650°C				
Mounting Options	Recessed				
	Solid Timber 30/60/90min, I-				
Part B Fire Rating	Joist 30min, Metal Web				
	30min				
Dimmer Type	1-10V				
Power Factor	0.80				

PHOTOMETRICS @ 25°C

Product code	Finish	Туре	w	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
BDB00F30NVI	Matt black RAL9017	White Baffle Slim Round Bezel	9.0W	3000K	15°	850	94	7816	A D

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable Required for Connector Type of Wiring Required 2 x twin & earth (6242Y 3x1.5mm?) or 3-core cable (R02V 3x1.5mm?) Parallel

ACCESSORIES

LEDEP10 LEDEP10DA 3hr non-maintained, self-test emergency pack (plug & play) Emergency converter, DALI-2 Addressable

Sold Separately Sold Separately



LIGHTING INNOVATION



DIM

CRI>80

Available in IP65 for various applications

Mains, 1-10V & DALI-2 dimmable options

CRI 90 providing true colour
appearance

WARRANTY

arranty

7 years

FEATURES & BENEFITS

The 1901 family consists of a pendant, spot light and downlight all with a consistent design language Use our product selector to choose from 1,800 different combinations Designed & assembled in Northampton UK Fixed, Adjustable, Round, Square, Trimless options available Emergency options available Fire-rated to 30 minutes for us in Solid timber, I-Joist and Metal Web ceiling joists Integrated LED using premium components to achieve 70,000 hours/60 years lifetime

BEAM ANGLE: 15°

