

1901 DOWNLIGHT

Design your light! Modular Architectural Downlight Range

FEATURES

IP rating	IP44	
CSP Switchable	Single CCT	
Tiltable	No	
UGR	UGR<19	
Dimmable Option	Yes (DALI-2)	
LED Lifetime	L70 70,000h CRI>90	
Colour Rendering Index		
Colour Consistency	SDCM3	
Emergency Option	Yes, using converter	
Rotation Angle	No	

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	400g
Insulation Coverable	No
Inrush Current	20A 17🛙 s
Cut Out Size	68-86 x2
Construction Material	Aluminium
UK Bathroom Zone	1
Maximum ceiling thickness	40 mm
SELV	Yes
Electric Class (1, 2, 3)	2
Suitable for coastal areas	No
Install Connector Type	Loop in / Loop out
UK Building Regulations	Part B, C, E, P & L
FR Building Regulations	Satisfait les essais au fil
rk building kegulations	incandescent: 650°C
Mounting Options	Recessed
	Solid Timber 30/60/90min, I-
Part B Fire Rating	Joist 30min, Metal Web
	30min
Dimmer Type	DALI Dimming
Power Factor	0.80

PHOTOMETRICS @ 25°C

Product code	Finish	Туре	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
BDB04F27ND	Matt black RAL9017	White Baffle Double Trimless	18W	2700K	15°	2 x 850	94	2 x 7214	A D

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable Required for Connector	2 x twin & earth (6242Y 3x1.5mm?) or 3-core cable (R02V 3x1.5mm?)
Type of Wiring Required	Parallel

ACCESSORIES

LEDEP10 LEDEP10DA

	3hr non-maintained, self-test emergency pack (plug & play)	Sold Separately
L Contraction of the second seco	Emergency converter, DALI-2 Addressable	Sold Separately



LIGHTING INNOVATION





CRI>80

WARRANTY

arranty

FEATURES & BENEFITS

BEAM ANGLE: 15°

