



collingwood



- IP65** Available in IP65 for various applications
- Dim** Mains, 1-10V & DALI-2 dimmable options
- >80Ra** CRI 80 providing true colour appearance

BDB04F27WD

Design your light! Modular Architectural Downlight Range

Features

IP rating	IP44
CSP Switchable	Single CCT
Tilttable	No
UGR	UGR<16, UGR<19, UGR<22
Dimmable Option	Yes (DALI-2)
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>90
Colour Consistency	SDCM3
Emergency Option	Yes, using converter
Rotation Angle	No

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	400g
Insulation Coverable	No
Inrush Current	20A 17ms
Cut Out Size	68-86 x2
Construction Material	Aluminium
UK Bathroom Zone	1
Maximum ceiling thickness	40 mm
SELV	Yes
Electric Class (1, 2, 3)	2
Suitable for coastal areas	No
Install Connector Type	Loop in / Loop out
UK Building Regulations	Part B, C, E, P & L
FR Building Regulations	Satisfait les essais au fil incandescent: 650°C
Mounting Options	Recessed
Part B Fire Rating	Solid Timber 30/60/90min, I-Joist 30min, Metal Web 30min
Dimmer Type	DALI Dimming
Power Factor	0.80

Guarantee

Warranty 7 years

Features & benefits

- The 1901 family consists of a pendant, spot light and downlight all with a consistent design language
- Use our product selector to choose from 1,800 different combinations
- Designed & assembled in Northampton UK
- Fixed, Adjustable, Round, Square, Trimless options available
- Emergency options available
- Fire-rated to 30 minutes for us in Solid timber, I-Joist and Metal Web ceiling joists
- Integrated LED using premium components to achieve 70,000 hours/60 years lifetime

Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
BDB04F27WD	Matt black RAL9017	White Baffle Double Trimless	19.2W	2700K	50°	2x575	60	2x985	

Energy rating is a reflection of the LED light source.

Wiring Information

Cable Required for Connector	2 x twin & earth (6242Y 3x1.5mm?) or 3-core cable (R02V 3x1.5mm?)
Type of Wiring Required	Parallel

Accessories

LEDEPI0	3hr non-maintained, self-test emergency pack (plug & play)	Sold Separately
LEDEPI0DA	Emergency converter, DALI-2 Addressable	Sold Separately

Beam angle: 50°

