

IP65 Available in IP65 for various applications

Dim Mains, 1-10V & DALI-2 dimmable options

>80Ra CRI 80 providing true colour appearance

Design your light! Modular Architectural Downlight Range

Features

Colour Rendering Index	CRI>90
Emergency Option	Yes, using converter


Installation Information

Input	220-240V AC
Construction Material	Aluminium
UK Bathroom Zone	N/A
Electric Class (1, 2, 3)	2
Suitable for coastal areas	No
Ceiling Joist Approvals	Solid timber, I-Joist and Metal Web
Power Factor	0.8

Guarantee

Warranty 7 years

Photometrics @ 25°C

Product Code	Energy
BDB10A27MD	

Wiring Information

Cable Required for Connector	2 x twin & earth (6242Y 3x1.5mm ²) or 3-core cable (R02V 3x1.5mm ²)
------------------------------	---

Accessories

LEDEP10	3hr non-maintained, self-test emergency pack (plug & play)	Sold Separately
LEDEP09DA	Emergency converter, DALI-2 Addressable, maintained	Sold Separately

Features & benefits

- The 1901 family consists of a pendant, spot light and downlight all with a consistent design language
- Use our product selector to choose from 1,800 different combinations
- Designed & assembled in Northampton UK
- Fixed, Adjustable, Round, Square, Trimless options available
- Emergency options available
- Fire-rated to 30 minutes for us in Solid timber, I-Joist and Metal Web ceiling joists
- Integrated LED using premium components to achieve 70,000 hours/60 years lifetime

Beam angle:

