

# 1901 DOWNLIGHT

Design your light! Modular Architectural Downlight Range

#### FEATURES

IP rating	IP65			
CSP Switchable	Single CCT			
Tiltable	No			
UGR	UGR<16			
Dimmable Option	Yes (DALI-2)			
LED Lifetime	L70 70,000h			
Colour Rendering Index	CRI>90			
Colour Consistency	SDCM3			
Emergency Option	Yes, using converter			
Rotation Angle	No			

## INSTALLATION INFORMATION

Input	220-240V AC			
Maximum Ambient Temperature	40°C			
Weight	260g			
Insulation Coverable	No			
Inrush Current	20A 17⊠s			
Cut Out Size	65-78			
Construction Material	Aluminium			
UK Bathroom Zone	1			
Maximum ceiling thickness	40 mm			
SELV	Yes			
Electric Class (1, 2, 3)	2			
Suitable for coastal areas	No			
Install Connector Type	Loop in / Loop out			
UK Building Regulations	Part B, C, E, P & L			
FR Building Regulations	Satisfait les essais au fil			
rk building kegulations	incandescent: 650°C			
Mounting Options	Recessed			
	Solid Timber 30/60/90min, I-			
Part B Fire Rating	Joist 30min, Metal Web			
	30min			
Dimmer Type	DALI Dimming			
Power Factor	0.80			

### PHOTOMETRICS @ 25°C

	Туре	w	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
BDB12F27NDI Matt bl RAL901		9.0W	2700K	15°	800	89	7214	A t D

Energy rating is a reflection of the LED light source.

#### WIRING INFORMATION

Cable Required for Connector Type of Wiring Required

 onnector
 2 x twin & earth (6242Y 3x1.5mm?) or 3-core cable (R02V 3x1.5mm?)

 red
 Parallel

#### ACCESSORIES

LEDEP10 LEDEP10DA 3hr non-maintained, self-test emergency pack (plug & play) Emergency converter, DALI-2 Addressable Sold Separately Sold Separately



#### LIGHTING INNOVATION

IP**65** 

CRI>80

Available in IP65 for various applications

Mains, 1-10V & DALI-2 dimmable options

CRI 90 providing true colour appearance

#### WARRANTY

irranty

7 years

## FEATURES & BENEFITS

The 1901 family consists of a pendant, spot light and downlight all with a consistent design language Use our product selector to choose from 1,800 different combinations Designed & assembled in Northampton UK Fixed, Adjustable, Round, Square, Trimless options available Emergency options available Fire-rated to 30 minutes for us in Solid timber, I-Joist and Metal Web ceiling joists Integrated LED using premium components to achieve 70,000 hours/60 years lifetime

BEAM ANGLE: 15°

