

1901 DOWNLIGHT

Design your light! Modular Architectural Downlight Range

FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Tiltable	No
UGR	UGR<16
Dimmable Option	Yes (1-10V)
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>90
Colour Consistency	SDCM3
Emergency Option	Yes, using converter
Rotation Angle	No

INSTALLATION INFORMATION

Input	220-240V AC			
Maximum Ambient Temperature	40°C			
Weight	400g			
Insulation Coverable	No			
Inrush Current	10A/22⊠s			
Cut Out Size	68-86 x2			
Construction Material	Aluminium			
UK Bathroom Zone	1			
Maximum ceiling thickness	40 mm			
SELV	Yes			
Electric Class (1, 2, 3)	2			
Suitable for coastal areas	No			
Install Connector Type	Loop in / Loop out			
UK Building Regulations	Part B, C, E, P & L			
FR Building Regulations	Satisfait les essais au fil			
rk building Regulations	incandescent: 650°C			
Mounting Options	Recessed			
	Solid Timber 30/60/90min, I-			
Part B Fire Rating	Joist 30min, Metal Web			
	30min			
Dimmer Type	1-10V			
Power Factor	0.80			

PHOTOMETRICS @ 25°C

Product code	Finish	Туре	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
BDB14F30MVI	Matt black RAL9017	Black Baffle Double Trimless	18W	3000K	24°	2 x 800	89	2 x 3250	A D

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable Required for Connector	2 x twin & earth (6242Y 3x1.5mm?) or 3-core cable (R02V 3x1.5mm?)
Type of Wiring Required	Parallel

ACCESSORIES

LEDEP10	3hr non-maintained, self-test emergency pack (plug & play)	Sold Separately
LEDEP10DA	Emergency converter, DALI-2 Addressable	Sold Separately

A COLLINGWOOD

LIGHTING INNOVATION







WARRANTY

Warranty

' years

FEATURES & BENEFITS

The 1901 family consists of a pendant, spot ligh and downlight all with a consistent design language

Use our product selector to choose from 1,800 different combinations

Designed & assembled in Northampton UK

Fixed, Adjustable, Round, Square, Trimless options available

Emergency options available

Fire-rated to 30 minutes for us in Solid timber, I Joist and Metal Web ceiling joists

Integrated LED using premium components to achieve 70,000 hours/60 years lifetime

BEAM ANGLE: 24°

