

1901 DOWNLIGHT

Design your light! Modular Architectural Downlight Range

FEATURES

IP rating	IP44				
CSP Switchable	Dim to Warm				
Tiltable (°)	Fixed				
UGR	UGR<16				
Dimmable Option	Yes (Mains)				
LED Lifetime	L70 70,000h				
Colour Rendering Index	CRI>90				
Colour Consistency	SDCM3				
Emergency Option	Yes, using converter				
Rotation angle (°)	Fixed				

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	260g
Insulation Coverable	No
Inrush Current	1.12A 10⊠s
Cut Out Size	65-78
Construction Material	Aluminium
UK Bathroom Zone	1
Maximum ceiling thickness	40 mm
SELV	Yes
Electric Class (1, 2, 3)	II
Suitable for coastal areas	No
Install Connector Type	Loop in / Loop out
UK Building Regulations	Part B, C, E, P & L
FR Building Regulations	Satisfait les essais au fil
rk building Regulations	incandescent: 650°C
Mounting Options	Recessed
	Solid Timber 30/60/90min, I-
Part B Fire Rating	Joist 30min, Metal Web
	30min
Power Factor	0.80

PHOTOMETRICS @ 25°C

Product code	Finish	Туре	w	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
BDL02F28MM	Matt white	White Baffle	10W	1800K -	24°	600	60	3148	A f G
	RAL9003	Square Bezel		3000K					G

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable Required for Connector	2 x twin & earth (6242Y 3x1.5mm?) or 3-core cable (R02V 3x1.5mm?)
Type of Wiring Required	Parallel

ACCESSORIES

LEDEP10	3hr non-maintained, self-test emergency pack (plug & play)	Sold Separately
LEDEP10DA	Emergency converter, DALI-2 Addressable	Sold Separately



LIGHTING INNOVATION



Available in IP65 for various applications



Mains, 1-10V & DALI-2 dimmable options



CRI 90 providing true colour appearance

WARRANTY

Warranty

7 yea

FEATURES & BENEFITS

The 1901 family consists of a pendant, spot ligh and downlight all with a consistent design language

Use our product selector to choose from 1,800 different combinations

Designed & assembled in Northampton UK

Fixed, Adjustable, Round, Square, Trimless options available

Emergency options available

Fire-rated to 30 minutes for us in Solid timber, I-Joist and Metal Web ceiling joists

Integrated LED using premium components to achieve 70,000 hours/60 years lifetime

PATENT: GB2576385 EP3648256 HK40014447

BEAM ANGLE: 24°

