

# 1901 DOWNLIGHT

Design your light! Modular Architectural Downlight Range

#### **FEATURES**

IP rating	IP44
CSP Switchable	Single CCT
Tiltable	No
UGR	UGR<16
Dimmable Option	Yes (DALI-2)
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>90
Colour Consistency	SDCM3
Emergency Option	Yes, using converter
Rotation Angle	No

#### INSTALLATION INFORMATION

Input	220-240V AC		
Maximum Ambient Temperature	40°C		
Weight	400g		
Insulation Coverable	No		
Inrush Current	20A 17⊠s		
Cut Out Size	68-86 x2		
Construction Material	Aluminium		
UK Bathroom Zone	1		
Maximum ceiling thickness	40 mm		
SELV	Yes		
Electric Class (1, 2, 3)	2		
Suitable for coastal areas	No		
Install Connector Type	Loop in / Loop out		
UK Building Regulations	Part B, C, E, P & L		
FR Building Regulations	Satisfait les essais au fil		
rk building kegulations	incandescent: 650°C		
Mounting Options	Recessed		
	Solid Timber 30/60/90min, I-		
Part B Fire Rating	Joist 30min, Metal Web		
	30min		
Dimmer Type	DALI Dimming		
Power Factor	0.80		

## PHOTOMETRICS @ 25°C

Product cod	e Finish	Туре	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
BDL14F27MI	Matt white RAL9003	Black Baffle Double Trimless	18W	2700K	24°	2 X 800	89	2 X 3250	A D

Energy rating is a reflection of the LED light source.

## WIRING INFORMATION

Cable Required for Connector	2 x twin & earth (6242Y 3x1.5mm?) or 3-core cable (R02V 3x1.5mm?)
Type of Wiring Required	Parallel

## **ACCESSORIES**

LEDEP10	3hr non-maintained, self-test emergency pack (plug & play)	Sold Separately
LEDEP10DA	Emergency converter, DALI-2 Addressable	Sold Separately



LIGHTING INNOVATION







#### WARRANTY

Warranty

' years

## FEATURES & BENEFITS

The 1901 family consists of a pendant, spot ligh and downlight all with a consistent design language

Use our product selector to choose from 1,800 different combinations

Designed & assembled in Northampton UK

Fixed, Adjustable, Round, Square, Trimless options available

Emergency options available

Fire-rated to 30 minutes for us in Solid timber, I Joist and Metal Web ceiling joists

Integrated LED using premium components to achieve 70,000 hours/60 years lifetime

BEAM ANGLE: 24°

