



collingwood



- IP65** Available in IP65 for various applications
- Dim** Mains, 1-10V & DALI-2 dimmable options
- >80Ra** CRI 80 providing true colour appearance

BDL14F40MV

Design your light! Modular Architectural Downlight Range

Features

IP rating	IP44
CSP Switchable	Single CCT
UGR	0
Dimmable Option	Yes (1-10V)
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>90
Colour Consistency	SDCM3
Emergency Option	Yes, using converter

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	400g
Insulation Coverable	No
Inrush Current	10A/220s
Cut Out Size	68-86 x2
Construction Material	Aluminium
UK Bathroom Zone	1
Maximum ceiling thickness	40 mm
SELV	SELV
Electric Class (1, 2, 3)	2
Suitable for coastal areas	No
Install Connector Type	Loop in / Loop out
UK Building Regulations	Part B, C, E, P & L
FR Building Regulations	Satisfait les essais au fil incandescent: 650°C
Mounting Options	Recessed
Ceiling Joist Approvals	Solid timber, I-Joist and Metal Web
Dimmer Type	1-10V
Power Factor	0.80

Guarantee

Warranty 7 years

Features & benefits

- The 1901 family consists of a pendant, spot light and downlight all with a consistent design language
- Use our product selector to choose from 1,800 different combinations
- Designed & assembled in Northampton UK
- Fixed, Adjustable, Round, Square, Trimless options available
- Emergency options available
- Fire-rated to 30 minutes for us in Solid timber, I-Joist and Metal Web ceiling joists
- Integrated LED using premium components to achieve 70,000 hours/60 years lifetime

Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
BDL14F40MV	Matt white RAL9003	Black Baffle Double Trimless	19.2W	4000K	24°	2 x 740	77	2 x 3595	

Wiring Information

Cable Required for Connector	2 x twin & earth (6242Y 3x1.5mm) or 3-core cable (R02V 3x1.5mm)
Type of Wiring Required	Parallel

LED Driver

Input	Dimming
220-240V	Yes

Accessories

LEDEP10	3hr non-maintained, self-test emergency pack (plug & play)	Sold Separately
LEDEP09DA	Emergency converter, DALI-2 Addressable, maintained	Sold Separately

Beam angle: 24°

