

1901 DOWNLIGHT

Design your light! Modular Architectural Downlight Range

FEATURES

IP rating	IP44
CSP Switchable	Single CCT
Tiltable	No
UGR	UGR<16
Dimmable Option	Yes (DALI-2)
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>90
Colour Consistency	SDCM3
Emergency Option	Yes, using converter
Rotation Angle	No

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	400g
Insulation Coverable	No
Inrush Current	20A 17🛙 s
Cut Out Size	68-86 x2
Construction Material	Anim Ambient Temperature 40°C 40°C the 40°G tion Coverable No Current 20A 17%s at Size 68-86 x2 ruction Material Aluminium throom Zone 1 num ceiling thickness 40 mm Yes ic Class (1, 2, 3) 2 close for coastal areas No I Connector Type Loop in / Loop out ilding Regulations Part B, C, E, P & L Cop in / Loop out ilding Regulations Recessed Solid Timber 30/60/90min, I- Joist 30min, Metal Web 30min er Type DALI Dimming
UK Bathroom Zone	1
Maximum ceiling thickness	40 mm
SELV	Yes
Electric Class (1, 2, 3)	2
Suitable for coastal areas	No
Install Connector Type	Loop in / Loop out
Weight 400g hsulation Coverable No hrush Current 20A 172s Cut Out Size 68-86 x2 Sconstruction Material Aluminium IK Bathroom Zone 1 Maximum ceiling thickness 40 mm ELV Yes Iectric Class (1, 2, 3) 2 uitable for coastal areas No NK Building Regulations Part B, C, E, P & L R Building Regulations Recessed Anama Part B, Fire Rating Solid Timber 30/60/90min, I- Joist 30min, Metal Web 30min 30min	
EP Puilding Populations	Satisfait les essais au fil
R Building Regulations incandescent: 650°C	
Mounting Options	Recessed
	Solid Timber 30/60/90min, I-
Part B Fire Rating	Joist 30min, Metal Web
	30min
Dimmer Type	DALI Dimming
Power Factor	0.80

PHOTOMETRICS @ 25°C

Product code	Finish	Туре	w	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
BDL14F40ND	Matt white RAL9003	Black Baffle Double Trimless	18W	4000K	15°	2 x 850	94	2 x 9018	A D

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Type of Wiring Required	Parallel
Cable Required for Connector	2 x twin & earth (6242Y 3x1.5mm?) or 3-core cable (R02V 3x1.5mm?)

ACCESSORIES

LEDEP10 LEDEP10DA

3hr non-maintained, self-test emergency pack (plug & play)	Sold Separately
Emergency converter, DALI-2 Addressable	Sold Separately



LIGHTING INNOVATION





CRI>80

WARRANTY

arranty

FEATURES & BENEFITS

BEAM ANGLE: 15°

