

1W at 350mA or 700mA

Coastal Protected

IP65 ideal for outdoor areas

## FEATURES & BENEFITS

Choice of wood finishes: Iroko, Sapele or Oak

Pointed, Chamfered or Domed top

Choice of low-voltage or straight-to-mains

Side-entry cable or base-entry cable options

Three colour temperature options: 2700K, 3000K or 4000K

7-year warranty



## BL01

Low voltage wood

### FEATURES

<b>IP rating</b>	IP65
<b>CSP Switchable</b>	Single CCT
<b>LED Lifetime</b>	L70 70,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Colour Consistency</b>	SDCM3

### INSTALLATION INFORMATION

<b>Input</b>	350mA / 700mA DC
<b>Maximum Ambient Temperature</b>	35°C
<b>Weight</b>	5800g
<b>Construction Material</b>	Sapele wood
<b>UK Bathroom Zone</b>	1
<b>Electric Class (1, 2, 3)</b>	III
<b>Suitable for coastal areas</b>	Yes (with appropriate treatment)

### PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
BL01FIS30	Natural	Single LED Chamfered	1W	3000K	26°	75	75	210	
			(350mA) / 2W			135	68	379	
			(700mA)			(700mA)	(700mA)	(700mA)	
BL01DIS30	Natural	Single LED Domed	1W	3000K	26°	75	75	210	
			(350mA) / 2W			135	68	379	
			(700mA)			(700mA)	(700mA)	(700mA)	
BL01PIS27	Natural	Single LED Pointed	1W	2700K	26°	70	70	204	
			(350mA) / 2W			120	60	337	
			(700mA)			(700mA)	(700mA)	(700mA)	
BL01PIS30	Natural	Single LED Pointed	1W	3000K	26°	75	75	210	
			(350mA) / 2W			135	68	379	
			(700mA)			(700mA)	(700mA)	(700mA)	
BL01PIS40	Natural	Single LED Pointed	1W	4000K	26°	95	95	267	
			(350mA) / 2W			140	70	393	
			(700mA)			(700mA)	(700mA)	(700mA)	
BL01FIB30	Natural	Single LED Chamfered	1W	3000K	26°	75	75	210	
			(350mA) / 2W			135	68	379	
			(700mA)			(700mA)	(700mA)	(700mA)	
BL01DIB27	Natural	Single LED Domed	1W	2700K	26°	70	70	204	
			(350mA) / 2W			120	60	337	
			(700mA)			(700mA)	(700mA)	(700mA)	
BL01DIB30	Natural	Single LED Domed	1W	3000K	26°	75	75	210	
			(350mA) / 2W			135	68	379	
			(700mA)			(700mA)	(700mA)	(700mA)	
BL01DIB40	Natural	Single LED Domed	1W	4000K	26°	95	95	267	
			(350mA) / 2W			140	70	393	
			(700mA)			(700mA)	(700mA)	(700mA)	

26°

Adding style and flair to any design scheme, bollards can add depth and dimension to a landscape. Made in Great Britain, this high-quality bollard is made from hardwearing and aesthetically pleasing Iroko wood with sleek chamfered top and features a single LED for a neat and concentrated beam of light. Perfect for use with driveways and pathways, this bollard can be purposely positioned in a uniformed capacity to highlight a space or integrated into a landscape feature. For added flexibility, we have provided two cable entry options - side or base - depending on whether the bollard will be recessed or surface mounted, and a choice between three white LED colour options.

<b>BL01PIB27</b>	Natural	Single LED Pointed	1W	2700K	26°	70	70	204	
			(350mA) / 2W (700mA)			(350mA) / 120 (700mA)	(350mA) / 60 (700mA)	(350mA) / 337 (700mA)	

## WIRING INFORMATION

<b>Cable / Flying Lead</b>	1.8m (H05RN-F) rubberised cable (outside diameter: 6mm)
<b>Type of Wiring Required</b>	Series
<b>Input Cable Type</b>	H05RN 0.75mm <sup>2</sup>

## LED DRIVER

Driver	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9				1	9
PLR/350 1-5				1	5
PLU/700 3-9	N/A	N/A	N/A	3	9

## ACCESSORIES

<b>BOL LED BRACKET</b>		Sold Separately
<b>JB2 / JB4 / JB6</b>	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
<b>WCR 275 BLACK</b>	2-core rubber cable	Sold Separately