

1W at 350mA or 700mA

Coastal Protected

IP65 ideal for outdoor areas

## FEATURES & BENEFITS

Choice of wood finishes: Iroko, Sapele or Oak

Pointed, Chamfered or Domed top

Choice of low-voltage or straight-to-mains

Side-entry cable or base-entry cable options

Three colour temperature options: 2700K, 3000K or 4000K

7-year warranty

# BL01

Low voltage wood










## FEATURES

IP rating	IP65
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

## INSTALLATION INFORMATION

Input	350mA / 700mA DC
Maximum Ambient Temperature	35°C
Weight	5800g
Construction Material	Sapele wood
UK Bathroom Zone	1
Electric Class (1, 2, 3)	III
Suitable for coastal areas	Yes (with appropriate treatment)

## PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
BL01FIS30	Natural	Single LED Chamfered	1W (350mA) / 2W (700mA)	3000K	26°	75 (350mA) / 135 (700mA)	75 (350mA) / 68 (700mA)	210 (350mA) / 379 (700mA)	
BL01DIS30	Natural	Single LED Domed	1W (350mA) / 2W (700mA)	3000K	26°	75 (350mA) / 135 (700mA)	75 (350mA) / 68 (700mA)	210 (350mA) / 379 (700mA)	
BL01PIS27	Natural	Single LED Pointed	1W (350mA) / 2W (700mA)	2700K	26°	70 (350mA) / 120 (700mA)	70 (350mA) / 60 (700mA)	204 (350mA) / 337 (700mA)	
BL01PIS30	Natural	Single LED Pointed	1W (350mA) / 2W (700mA)	3000K	26°	75 (350mA) / 135 (700mA)	75 (350mA) / 68 (700mA)	210 (350mA) / 379 (700mA)	
BL01PIS40	Natural	Single LED Pointed	1W (350mA) / 2W (700mA)	4000K	26°	95 (350mA) / 140 (700mA)	95 (350mA) / 70 (700mA)	267 (350mA) / 393 (700mA)	
BL01FIB30	Natural	Single LED Chamfered	1W (350mA) / 2W (700mA)	3000K	26°	75 (350mA) / 135 (700mA)	75 (350mA) / 68 (700mA)	210 (350mA) / 379 (700mA)	
BL01DIB27	Natural	Single LED Domed	1W (350mA) / 2W (700mA)	2700K	26°	70 (350mA) / 120 (700mA)	70 (350mA) / 60 (700mA)	204 (350mA) / 337 (700mA)	
BL01DIB30	Natural	Single LED Domed	1W (350mA) / 2W (700mA)	3000K	26°	75 (350mA) / 135 (700mA)	75 (350mA) / 68 (700mA)	210 (350mA) / 379 (700mA)	
BL01DIB40	Natural	Single LED Domed	1W (350mA) / 2W (700mA)	4000K	26°	95 (350mA) / 140 (700mA)	95 (350mA) / 70 (700mA)	267 (350mA) / 393 (700mA)	

BL01PIB27	Natural	Single LED Pointed	1W	2700K	26°	70	70	204	
			(350mA) /			(350mA) /	(350mA) /	(350mA) /	
			2W (700mA)			120 (700mA)	60 (700mA)	337 (700mA)	

## WIRING INFORMATION

<b>Cable / Flying Lead</b>	1.8m (H05RN-F) rubberised cable (outside diameter: 6mm)
<b>Type of Wiring Required</b>	Series
<b>Input Cable Type</b>	H05RN 0.75mm <sup>2</sup>

## LED DRIVER

Driver	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	N/A	N/A	N/A	1	9
PLR/350 1-5				1	5
PLU/700 3-9				3	9

## ACCESSORIES

<b>BOL LED BRACKET</b>		Sold Separately
<b>JB2 / JB4 / JB6</b>	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
<b>WCR 275 BLACK</b>	2-core rubber cable	Sold Separately

Adding style and flair to any design scheme, bollards can add depth and dimension to a landscape. Made in Great Britain, this high-quality bollard is made from hardwearing and aesthetically pleasing Iroko wood with sleek chamfered top and features a single LED for a neat and concentrated beam of light. Perfect for use with driveways and pathways, this bollard can be purposely positioned in a uniformed capacity to highlight a space or integrated into a landscape feature. For added flexibility, we have provided two cable entry options - side or base - depending on whether the bollard will be recessed or surface mounted, and a choice between three white LED colour options.