

1W 1W at 350mA or 700mA

Coastal Protected

IP65 IP65 ideal for outdoor areas

BL01

Low voltage wood

Features

IP rating	IP65
IK rating	N/A
CSP Switchable	Single CCT
Sensor Option	No
Dimmable Option	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

Installation Information

Input	350mA / 700mA
Maximum Ambient Temperature	35°C
Weight	5800g
Construction Material	Iroko wood
UK Bathroom Zone	1
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes (with appropriate treatment)

Guarantee


Warranty 7 years

Features & benefits

- Choice of wood finishes: Iroko, Sapele or Oak
- Pointed, Chamfered or Domed top
- Choice of low-voltage or straight-to-mains
- Side-entry cable or base-entry cable options
- Three colour temperature options: 2700K, 3000K or 4000K
- 7-year warranty

Photometrics @ 25°C

Product Code	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
BL01FIS30	Single LED Chamfered	1W (350mA) / 2W (700mA)	3000K	26°	75 (350mA) / 135 (700mA)	75 (350mA) / 68 (700mA)	210 (350mA) / 379 (700mA)	AIG F
BL01DIS30	Single LED Domed	1W (350mA) / 2W (700mA)	3000K	26°	75 (350mA) / 135 (700mA)	75 (350mA) / 68 (700mA)	210 (350mA) / 379 (700mA)	AIG F
BL01PIS27	Single LED Pointed	1W (350mA) / 2W (700mA)	2700K	26°	70 (350mA) / 120 (700mA)	70 (350mA) / 60 (700mA)	204 (350mA) / 337 (700mA)	AIG F
BL01PIS30	Single LED Pointed	1W (350mA) / 2W (700mA)	3000K	26°	75 (350mA) / 135 (700mA)	75 (350mA) / 68 (700mA)	210 (350mA) / 379 (700mA)	AIG F
BL01PIS40	Single LED Pointed	1W (350mA) / 2W (700mA)	4000K	26°	95 (350mA) / 140 (700mA)	95 (350mA) / 70 (700mA)	267 (350mA) / 393 (700mA)	AIG F
BL01FIB30	Single LED Chamfered	1W (350mA) / 2W (700mA)	3000K	26°	75 (350mA) / 135 (700mA)	75 (350mA) / 68 (700mA)	210 (350mA) / 379 (700mA)	AIG F
BL01DIB27	Single LED Domed	1W (350mA) / 2W (700mA)	2700K	26°	70 (350mA) / 120 (700mA)	70 (350mA) / 60 (700mA)	204 (350mA) / 337 (700mA)	AIG F
BL01DIB30	Single LED Domed	1W (350mA) / 2W (700mA)	3000K	26°	75 (350mA) / 135 (700mA)	75 (350mA) / 68 (700mA)	210 (350mA) / 379 (700mA)	AIG F
BL01DIB40	Single LED Domed	1W (350mA) / 2W (700mA)	4000K	26°	95 (350mA) / 140 (700mA)	95 (350mA) / 70 (700mA)	267 (350mA) / 393 (700mA)	AIG F
BL01PIB27	Single LED Pointed	1W (350mA) / 2W (700mA)	2700K	26°	70 (350mA) / 120 (700mA)	70 (350mA) / 60 (700mA)	204 (350mA) / 337 (700mA)	AIG F





collingwood

Wiring Information

Cable / Flying Lead	1.8m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN 0.75mm ²

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone
DRV150700 (all settings)	220-240V	Yes	No	N/A
DRV350700TD (350 & 500mA)	220-240V	Yes	Yes	N/A

Accessories

BOL LED BRACKET	Stainless steel bracket for BOL LED range	Sold Separately
JB2 / JB4 / JB6	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately

Adding style and flair to any design scheme, bollards can add depth and dimension to a landscape. Made in Great Britain, this high-quality bollard is made from hardwearing and aesthetically pleasing Iroko wood with sleek chamfered top and features a single LED for a neat and concentrated beam of light. Perfect for use with driveways and pathways, this bollard can be purposely positioned in a uniformed capacity to highlight a space or integrated into a landscape feature. For added flexibility, we have provided two cable entry options - side or base - depending on whether the bollard will be recessed or surface mounted, and a choice between three white LED colour options.