



## BL01

Low voltage wood

### FEATURES

IP rating	IP65
IK rating	N/A
CSP Switchable	Single CCT
Sensor Option	No
Dimmable Option	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

### INSTALLATION INFORMATION

Input	350mA / 700mA
Maximum Ambient Temperature	35°C
Weight	5800g
Inrush Current	N/A
Construction Material	Iroko wood
UK Bathroom Zone	1
SELV	N/A
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes (with appropriate treatment)

### PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
BL01FIS30	Natural	Single LED Chamfered	1W (350mA) / 2W (700mA)	3000K	26°	75 (350mA) / 135 (700mA)	75 (350mA) / 68 (700mA)	210 (350mA) / 379 (700mA)	
BL01DIS30	Natural	Single LED Domed	1W (350mA) / 2W (700mA)	3000K	26°	75 (350mA) / 135 (700mA)	75 (350mA) / 68 (700mA)	210 (350mA) / 379 (700mA)	
BL01PIS27	Natural	Single LED Pointed	1W (350mA) / 2W (700mA)	2700K	26°	70 (350mA) / 120 (700mA)	70 (350mA) / 60 (700mA)	204 (350mA) / 337 (700mA)	
BL01PIS30	Natural	Single LED Pointed	1W (350mA) / 2W (700mA)	3000K	26°	75 (350mA) / 135 (700mA)	75 (350mA) / 68 (700mA)	210 (350mA) / 379 (700mA)	
BL01PIS40	Natural	Single LED Pointed	1W (350mA) / 2W (700mA)	4000K	26°	95 (350mA) / 140 (700mA)	95 (350mA) / 70 (700mA)	267 (350mA) / 393 (700mA)	
BL01FIB30	Natural	Single LED Chamfered	1W (350mA) / 2W (700mA)	3000K	26°	75 (350mA) / 135 (700mA)	75 (350mA) / 68 (700mA)	210 (350mA) / 379 (700mA)	
BL01DIB27	Natural	Single LED Domed	1W (350mA) / 2W (700mA)	2700K	26°	70 (350mA) / 120 (700mA)	70 (350mA) / 60 (700mA)	204 (350mA) / 337 (700mA)	
BL01DIB30	Natural	Single LED Domed	1W (350mA) / 2W (700mA)	3000K	26°	75 (350mA) / 135 (700mA)	75 (350mA) / 68 (700mA)	210 (350mA) / 379 (700mA)	
BL01DIB40	Natural	Single LED Domed	1W (350mA) / 2W (700mA)	4000K	26°	95 (350mA) / 140 (700mA)	95 (350mA) / 70 (700mA)	267 (350mA) / 393 (700mA)	

1W

1W at 350mA or 700mA



Coastal Protected

IP65

IP65 ideal for outdoor areas

### WARRANTY

Warranty

7 years

### FEATURES & BENEFITS

Choice of wood finishes: Iroko, Sapele or Oak

Pointed, Chamfered or Domed top

Choice of low-voltage or straight-to-mains

Side-entry cable or base-entry cable options

Three colour temperature options: 2700K, 3000K or 4000K

7-year warranty

Adding style and flair to any design scheme, bollards can add depth and dimension to a landscape. Made in Great Britain, this high-quality bollard is made from hardwearing and aesthetically pleasing Iroko wood with sleek chamfered top and features a single LED for a neat and concentrated beam of light. Perfect for use with driveways and pathways, this bollard can be purposely positioned in a uniformed capacity to highlight a space or integrated into a landscape feature. For added flexibility, we have provided two cable entry options - side or base - depending on whether the bollard will be recessed or surface mounted, and a choice between three white LED colour options.

			2W (700mA)			140 (700mA)	70 (700mA)	393 (700mA)	
<b>BLO1PIB27</b>	Natural	Single LED Pointed	1W (350mA) / 2W (700mA)	2700K	26°	70 (350mA) / 120 (700mA)	70 (350mA) / 60 (700mA)	204 (350mA) / 337 (700mA)	

## WIRING INFORMATION

<b>Cable / Flying Lead</b>	1.8m (H05RN-F) rubberised cable (outside diameter: 6mm)
<b>Type of Wiring Required</b>	Series
<b>Input Cable Type</b>	H05RN 0.75mm <sup>2</sup>

## LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone
DRV150700 (all settings)	220-240V	Yes	No	N/A
DRV350700TD (350 & 500mA)	220-240V	Yes	Yes	N/A

## ACCESSORIES

<b>BOL LED BRACKET</b>	Stainless steel bracket for BOL LED range	Sold Separately
<b>JB2 / JB4 / JB6</b>	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
<b>WCR 275 BLACK</b>	2-core rubber cable	Sold Separately