

BL03

Straight to mains

FEATURES

IP rating	IP65	
IK rating	N/A	
CSP Switchable	Single CCT	
Sensor Option	No	
Dimmable Option	No	
LED Lifetime	L70 70,000h	
Colour Rendering Index	CRI>80	
Colour Consistency	SDCM3	

INSTALLATION INFORMATION

Input	220-240V AC	
Maximum Ambient Temperature	35°C	
Weight	5500g	
Inrush Current	60A 0.037ms	
Construction Material	Iroko wood	
UK Bathroom Zone	N/A	
SELV	Yes	
Electric Class (1, 2, 3)	2	
Earth Leakage	0.1mA	
Suitable for coastal areas	Yes (with appropriate	
Suitable for coastal areas	treatment)	

PHOTOMETRICS @ 25°C

BL03FIS27 Triple LED Chamfered 5W 2700K 110° 156 31 78 \$\frac{1}{6}\$ F BL03FIS30 Triple LED Chamfered 5W 3000K 110° 160 32 80 \$\frac{1}{6}\$ F
Triple LED 5W 2000K 110° 160 32 80 A
Chamfered SW 3000K 110 100 32 00 6
BL03FIS40 Triple LED Chamfered 5W 4000K 110° 246 49 104 10 F
BL03DIS27 Triple LED Domed 5W 2700K 110° 156 31 78
BL03DIS30 Triple LED Domed 5W 3000K 110° 160 32 80
BL03PIS27 Triple LED Pointed 5W 2700K 110° 156 31 78
BL03PIS30 Triple LED Pointed 5W 3000K 110° 160 32 80
BL03PIS40 Triple LED Pointed 5W 4000K 110° 246 49 104
BL03FiB30 Triple LED Chamfered 5W 3000K 110° 160 32 80 16 F
BL03DIB30 Triple LED Domed 5W 3000K 110° 160 32 80 16 F

WIRING INFORMATION

 Cable / Flying Lead
 NEW 1.5mm SY 2 Core PVC Steel Braid Cable. 2M Length.

 Type of Wiring Required
 Parallel

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes	N/A	N/A
ACCESSORIES				
BOL LED BRACKET	Stainless steel bracket for BOL LED range			Sold Separately
JB5	Gel filled junction box			Sold Separately



LIGHTING INNOVATION



5W at 350mA or 700mA



Coastal Protected



IP65 ideal for outdoor areas

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Choice of wood finishes: Iroko, Sapele or Oak

Pointed, Chamfered or Domed top

Choice of low-voltage or straight-to-mains

Side-entry cable or base-entry cable option

Three colour temperature options: 2700K, 3000K or 4000K
