

## FEATURES & BENEFITS

Choice of wood finishes: Iroko, Sapele or Oak

Pointed, Chamfered or Domed top

Choice of low-voltage or straight-to-mains

Side-entry cable or base-entry cable options

Three colour temperature options: 2700K, 3000K or 4000K

7 year warranty



# BL03

Straight to mains

## FEATURES

<b>IP rating</b>	IP65
<b>CSP Switchable</b>	Single CCT
<b>LED Lifetime</b>	L70 70,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Colour Consistency</b>	SDCM3

## INSTALLATION INFORMATION

<b>Input</b>	220-240V AC
<b>Maximum Ambient Temperature</b>	35°C
<b>Weight</b>	5500g
<b>Inrush Current</b>	60A 0.037ms
<b>Construction Material</b>	Sapele wood
<b>Electric Class (1, 2, 3)</b>	II
<b>Suitable for coastal areas</b>	Yes (with appropriate treatment)

## PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
BL03FIS27	Natural	Triple LED Chamfered	5W	2700K	110°	156	31	78	
BL03FIS30	Natural	Triple LED Chamfered	5W	3000K	110°	160	32	80	
BL03FIS40	Natural	Triple LED Chamfered	5W	4000K	110°	246	49	104	
BL03DIS27	Natural	Triple LED Domed	5W	2700K	110°	156	31	78	
BL03DIS30	Natural	Triple LED Domed	5W	3000K	110°	160	32	80	
BL03PIS27	Natural	Triple LED Pointed	5W	2700K	110°	156	31	78	
BL03PIS30	Natural	Triple LED Pointed	5W	3000K	110°	160	32	80	
BL03PIS40	Natural	Triple LED Pointed	5W	4000K	110°	246	49	104	
BL03FIB30	Natural	Triple LED Chamfered	5W	3000K	110°	160	32	80	
BL03DIB30	Natural	Triple LED Domed	5W	3000K	110°	160	32	80	

110°

## WIRING INFORMATION

<b>Cable / Flying Lead</b>	NEW 1.5mm SY 2 Core PVC Steel Braid Cable. 2M Length.
<b>Type of Wiring Required</b>	Parallel

## LED DRIVER

<b>Driver</b>	N/A (integrated SELV driver)
---------------	------------------------------

## ACCESSORIES

<b>BOL LED BRACKET</b>	Sold Separately
<b>JB5</b>	Gel filled junction box Sold Separately