

FEATURES & BENEFITS

Choice of wood finishes: Iroko, Sapele or Oak

Pointed, Chamfered or Domed top

Choice of low-voltage or straight-to-mains

Side-entry cable or base-entry cable options

Three colour temperature options: 2700K, 3000K or 4000K

7 year warranty



BL03

Straight to mains

FEATURES

IP rating	IP65
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	35°C
Weight	5500g
Inrush Current	60A 0.037ms
Construction Material	Sapele wood
Electric Class (1, 2, 3)	II
Suitable for coastal areas	Yes (with appropriate treatment)

PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
BL03FIS27	Natural	Triple LED Chamfered	5W	2700K	110°	156	31	78	
BL03FIS30	Natural	Triple LED Chamfered	5W	3000K	110°	160	32	80	
BL03FIS40	Natural	Triple LED Chamfered	5W	4000K	110°	246	49	104	
BL03DIS27	Natural	Triple LED Domed	5W	2700K	110°	156	31	78	
BL03DIS30	Natural	Triple LED Domed	5W	3000K	110°	160	32	80	
BL03PIS27	Natural	Triple LED Pointed	5W	2700K	110°	156	31	78	
BL03PIS30	Natural	Triple LED Pointed	5W	3000K	110°	160	32	80	
BL03PIS40	Natural	Triple LED Pointed	5W	4000K	110°	246	49	104	
BL03FIB30	Natural	Triple LED Chamfered	5W	3000K	110°	160	32	80	
BL03DIB30	Natural	Triple LED Domed	5W	3000K	110°	160	32	80	

WIRING INFORMATION

Cable / Flying Lead	NEW 1.5mm SY 2 Core PVC Steel Braid Cable. 2M Length.
Type of Wiring Required	Parallel

LED DRIVER

Driver	N/A (integrated SELV driver)
---------------	------------------------------

ACCESSORIES

BOL LED BRACKET	Sold Separately
JB5	Gel filled junction box Sold Separately