



BOL100 Midi Post Light

Features IP rating IP54 IK rating IK04 **CSP Switchable** Single CCT Sensor Option No Dimmable Option **LED Lifetime** L70 30,000h Colour Rendering Index CRI>80 Colour Consistency SDCM4

| Installation Information | | | |
|-----------------------------|-----------------|--|--|
| Input | 220-240V AC | | |
| Maximum Ambient Temperature | 40°C | | |
| Weight | 1.2kg | | |
| Inrush Current | 20A | | |
| Construction Material | Aluminium / PVC | | |
| UK Bathroom Zone | 2 | | |
| SELV | Yes | | |
| Electric Class (1, 2, 3) | 1 | | |
| Earth Leakage | 0.1mA | | |
| Suitable for coastal areas | No | | |

Photometrics @ 25°C

| Product Code | Finish | Туре | W | Colour | Beam | lm | lm/W | Lx @ 1m | Energy |
|--------------|---------------|-------|-----|--------|------|-----|------|---------|--------|
| BOL100X30 | Black RAL9011 | 350mm | 11W | 3000K | 360° | 610 | 55 | 92 | å F |

Wiring Information

| Cable Required for Connector | 3x 1.0mm ² |
|------------------------------|-----------------------|
| Type of Wiring Required | Parallel |

LED Driver

| Driver | Input | SELV | Dimming | Bathroom Zone | Min | Max |
|------------------------------|----------|------|---------|---------------|-----|-----|
| N/A (integrated SELV driver) | 220-240V | Yes | No | 2 | - | - |

Accessories

| JB5 | Waterproof junction box / Gel filled waterproof connectors | Sold Separately |
|-----|---|-----------------|
| JDO | waterproof function pox / Ger filled waterproof conflectors | 3010 Separately |

collingwood



11W



IP54 ideal for walk ways and step



Benefiting from light all round with a 360° beam angle

Guarantee

Warranty 5 years

Features & benefits

- Straight to mains screw terminals
- Ideal for residential landscape projects, such as lighting low level shrubs
- Ideal to light up car parking spaces and
- High lumen output of 610lm
- Great for soft illumination onto stone paths
- Black RAL 9011



cologgwoodled



ongwoodlighting