



BOL101 Post Light

Straight to mains IP54, 610lm post light

Features

IP rating	IP54
IK rating	IK04
CSP Switchable	Single CCT
Sensor Option	No
Dimmable Option	No
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	1.5Kg
Inrush Current	20A
Construction Material	Aluminium / PVC
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	No

Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
BOL101X30	Black RAL9011	650mm	11W	3000K	360°	610	55	92	

Wiring Information

Cable Required for Connector	3x 1.0mm ²
Type of Wiring Required	Parallel

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes	No	2

Accessories

JB5	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
-----	--	-----------------



collingwood



11W



IP54 ideal for walk ways and step lighting



Benefiting from light all round with a 360° beam angle

Guarantee

Warranty 5 years

Features & benefits

- Straight to mains screw terminals
- Ideal for residential landscape projects, such as lighting low level shrubs
- Ideal to light up car parking spaces and driveways
- High lumen output of 610lm
- Great for soft illumination onto stone paths
- Black RAL 9011

Ø80mm

