



BOL101 Post Light

Straight to mains IP54, 610lm post light

Features

| | |
|------------------------|-------------|
| IP rating | IP54 |
| IK rating | IK04 |
| CSP Switchable | Single CCT |
| Sensor Option | No |
| Dimmable Option | No |
| LED Lifetime | L70 30,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM4 |

Installation Information

| | |
|-----------------------------|-----------------|
| Input | 220-240V AC |
| Maximum Ambient Temperature | 40°C |
| Weight | 1.5Kg |
| Inrush Current | 20A |
| Construction Material | Aluminium / PVC |
| UK Bathroom Zone | 2 |
| SELV | Yes |
| Electric Class (1, 2, 3) | 1 |
| Earth Leakage | 0.1mA |
| Suitable for coastal areas | No |

Photometrics @ 25°C

| Product Code | Finish | Type | W | Colour | Beam | lm | lm/W | Lx @ 1m | Energy |
|--------------|---------------|-------|-----|--------|------|-----|------|---------|--------|
| BOL101X30 | Black RAL9011 | 650mm | 11W | 3000K | 360° | 610 | 55 | 92 | |

Wiring Information

| | |
|------------------------------|-----------------------|
| Cable Required for Connector | 3x 1.0mm ² |
| Type of Wiring Required | Parallel |

LED Driver

| Driver | Input | SELV | Dimming | Bathroom Zone |
|------------------------------|----------|------|---------|---------------|
| N/A (integrated SELV driver) | 220-240V | Yes | No | 2 |

Accessories

| | | |
|-----|--|-----------------|
| JB5 | Waterproof junction box / Gel filled waterproof connectors | Sold Separately |
|-----|--|-----------------|



collingwood



11W



IP54 ideal for walk ways and step lighting



Benefiting from light all round with a 360° beam angle

Guarantee

Warranty 5 years

Features & benefits

- Straight to mains screw terminals
- Ideal for residential landscape projects, such as lighting low level shrubs
- Ideal to light up car parking spaces and driveways
- High lumen output of 610lm
- Great for soft illumination onto stone paths
- Black RAL 9011

