



23W

23W

IP65

IP65 ideal for car parks and walk ways

360°

Benefiting from light all round with a 360° beam angle

## BOL200 Midi Bollard

Straight to mains, IP65, 930lm bollard

### Features

IP rating	IP65
IK rating	IK04
CSP Switchable	Single CCT
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4

### Installation Information

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	2.6Kg
Inrush Current	20A 0.5ms
Construction Material	Aluminium / PVC
UK Bathroom Zone	2
SELV	SELV
Electric Class (1, 2, 3)	1
Earth Leakage	0.2mA
Suitable for coastal areas	No

### Guarantee

Warranty 5 years

### Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
BOL200X30	Black RAL9011	500mm	23W	3000K	360°	930	40	108	

### Wiring Information

Cable Required for Connector	3x 1.0mm <sup>2</sup>
Type of Wiring Required	Parallel

### LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (Integrated SLEV driver)	220-240V	Yes	No	2

### Accessories

JB5	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
-----	--	-----------------

### Features & benefits

- Straight to mains screw terminals
- Frosted window effect at the top
- Low glare illumination, ideal for pathways, boundary marking, or general illumination of exterior spaces
- High lumen output of 930lm

