



## BOL300 MIDI BOLLARD

Straight to mains, IP65, 500lm bollard

### FEATURES

IP rating	IP65
IK rating	IK08
CSP Switchable	Single CCT
Sensor Option	No
Dimmable Option	No
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4

### INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	2.9Kg
Inrush Current	20A
Construction Material	Aluminium / PVC
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.2mA
Suitable for coastal areas	No

### PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
<b>BOL300X30</b>	Black RAL9011	500mm	23W	3000K	360°	500	22	144	

### WIRING INFORMATION

Cable Required for Connector	3x 1.0mm <sup>2</sup>
Type of Wiring Required	Parallel

### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes	No	2

### ACCESSORIES

<b>JB5</b>	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
------------	--	-----------------

**23W** 23W

**IP65** IP65 ideal for car parks and walk ways

Benefiting from light all round with a 360° beam angle

### WARRANTY

Warranty 5 years

### FEATURES & BENEFITS

Straight to mains screw terminals

Domed top for a low glare finish, and a minimum up spill of light making it comfortable on the eye

IK08 rated

Black RAL 9011

