



BOL301 Bollard



collingwood



23W



IP65 ideal for car parks and walk ways



Benefiting from light all round with a 360° beam angle

Features

IP rating	IP65
IK rating	IK08
CSP Switchable	Single CCT
Sensor Option	No
Dimmable Option	No
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	4.6Kg
Inrush Current	20A
Construction Material	Aluminium / PVC
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.2mA
Suitable for coastal areas	No

Guarantee

Warranty 5 years

Features & benefits

- Straight to mains screw terminals
- Domed top for a low glare finish, and a minimum up spill of light making it comfortable on the eye
- Comes complete with root mounting kit
- IK08 rated
- Black RAL 9011

Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
BOL301X30	Black RAL9011	900mm	23W	3000K	360°	500	22	144	

Wiring Information

Cable Required for Connector	3x 1.0mm ²
Type of Wiring Required	Parallel

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes	No	2

Accessories

JB5	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
-----	--	-----------------

