



BOL301 Bollard

Straight to mains, IP65, 500lm bollard

Features

IP rating	IP65
IK rating	IK08
CSP Switchable	Single CCT
Sensor Option	No
Dimmable Option	No
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	4.6Kg
Inrush Current	20A
Construction Material	Aluminium / PVC
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.2mA
Suitable for coastal areas	No

Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
BOL301X30	Black RAL9011	900mm	23W	3000K	360°	500	22	144	

Wiring Information

Cable Required for Connector	3x 1.0mm ²
Type of Wiring Required	Parallel

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes	No	2

Accessories

JB5	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
-----	--	-----------------



collingwood

23W

23W

IP65

IP65 ideal for car parks and walk ways

360°

Benefiting from light all round with a 360° beam angle

Guarantee

Warranty 5 years

Features & benefits

- Straight to mains screw terminals
- Domed top for a low glare finish, and a minimum up spill of light making it comfortable on the eye
- Comes complete with root mounting kit
- IK08 rated
- Black RAL 9011

