


130lm/W High efficacy of 130lm/W

 Suspended gear tray for easy installation

EM Emergency option available

WARRANTY

Warranty	5 years
Battery Warranty	2 years
On-Site Warranty	2 years

FEATURES & BENEFITS

Multiple fixing points and several wiring options

Flicker free

Ideal for sheds, garages and warehouses

MW sensing range adjustable, up to 4m high, 8m diameter

Diffuser is released by side buttons and is easily accessible through loop-in/loop-out terminals



BOREALIS 5FT TWIN

5ft Twin, LED Batten


FEATURES

IP rating	IP20
IK rating	IK06
CSP Switchable	Single CCT
UGR	UGR<26
Sensor Option	On-Off Microwave sensor & daylight switching available
Dimmable Option	Yes (DALI-2, 0-10V)
LED Lifetime	L70 54,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6
Emergency Option	Yes, Manual and DALI-2 Test

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 40°C
Weight	1.77Kg, EM Version: 2.03Kg
Inrush Current	20A 0,2ms
Construction Material	Steel body, white powder coating PC opal diffuser
SELV	Yes
Electric Class (1, 2, 3)	1
Install Connector Type	Loop in / Loop out
UK Building Regulations	Part P
Mounting Options	Surface
Power Factor	0.95

PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	lm/W	EM lm	Lx @ 1m	Energy
BT5TS40	White	Standard	54W	4000K		7020	130	-	1894	
BT5TS40EM	White	Emergency	54W	4000K		7020	130	250	1894	
BT5TD40	White	DALI-2 dimmable	54W	4000K	120°	7020	130	-	1894	
BT5TD40EM	White	Emergency DALI-2 dimmable	54W	4000K	120°	7020	130	250	1894	
BT5TV40	White	1-10V dimmable	54W	4000K	120°	7020	130	-	1894	

WIRING INFORMATION

Cable Required for Connector	H05RN-F cable diameter 4 - 10mm, max conductor size 3x 1.5mm ²
Type of Wiring Required	Parallel
Input Cable Type	Max conductor cross section 1.5mm ²

ACCESSORIES

BT SK1	Suspension Kit - 2 steel wires, with holders.	Sold Separately
PIR BOLT	On-off PIR sensor with daylight switch	Sold Separately
PIR BOLT DIM	Dimming PIR Sensor with Lux Level switch 0-2000lx	Sold Separately
PIR BOLT DIM R	Remote control for use with PIR BOLT DIM	Sold Separately
EMBOLT MOPEN	Bolt-on emg conversion pack, Man-Test, 200lm	Sold Separately
EMBOLT M COR	Bolt-on emg conversion pack, Man-Test, 200lm	Sold Separately
EMBOLT SOPEN	Bolt-on emg conversion pack, Self-Test, 200lm	Sold Separately

1524mm

70mm
76mm