



CASAMBI WIRELESS CEILING SENSOR

Recessed or Surface mounted PIR+Daylight sensor for use up to 4m

FEATURES

IP rating	IP20
Dimmable Option	Yes (0-10V)

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 60°C
Electric Class (1, 2, 3)	II
Install Connector Type	Push-fit terminals 0,5 -
	1,5mm²
UK Building Regulations	Part P & L
Dimmer Type	App controlled

PHOTOMETRICS @ 25°C

P	roduct code	Finish
C	CASRECW	White

ACCESSORIES

Use as Sensor within the Mesh	Requires 0-10V driver	Sold Separately
Surface	Mounting Kit	Included



LIGHTING INNOVATION



Casambi Ready



Bluetooth Mesh



Wireless Control

WARRANTY

Marrant

5 years

FEATURES & BENEFITS

Casambi's Bluetooth Low Energy (BLE) system eliminates the need for control wiring, allowing for quick and easy installation in any project.

All nodes are connected to one another, eliminating the need for a single router setup

Simplified Installation – No extra control wiring, gateways, or routers needed

Fast Commissioning – Configure and adjust settings via the Casambi App

4-5m cone detection pattern when installed at 3m

