

CCDRV100DMX

100W DMX Driver

INSTALLATION INFORMATION

| Input | 220-240V AC | |
|-----------------------------|-------------------------------|--|
| Maximum Ambient Temperature | -25°C - 40°C | |
| Inrush Current | COLD START Max. 50A at 230VAC | |
| UK Bathroom Zone | 2 | |
| SELV | Yes | |
| Electric Class (1, 2, 3) | II | |
| Power Factor | 0.9 | |
| Power Pactor | 0.7 | |

Electrical Characteristics

| Driver Rated Wattage | Driver Input Voltage | Drive Current | Driver Output Voltage | Power Factor |
|----------------------|----------------------|---------------|-----------------------|--------------|
| 100 | 100-240V AC | max 4.16A | 24 | 0.9 |

ACCESSORIES

LEDRGBWEXT CR505RGBW Colour Change 5-core extension lead for RGBW products 5-Core RGBW ribbon cable Sold Separately Sold Separately



LIGHTING INNOVATION

All-in-one Driver for RGBW/RGB Systems

24v DC Output

Receives DMX signal

WARRANTY

anty

FEATURES & BENEFITS

4 channel 24V DC Constant Voltage Output Multiple control inputs Max. 4.16A/CH, CH1+CH2+CH3+CH4=4.16A