



collingwood

All-in-one Driver for RGBW/RGB Systems

24v DC Output

Receives RF signal

CCDRV100RF

Installation Information	
Input	220-240V AC
Maximum Ambient Temperature	-25°C - 40°C
Inrush Current	COLD START Max. 50A at 230VAC
UK Bathroom Zone	1
SELV	Yes
Electric Class (1, 2, 3)	2
Power Factor	0.9

Electrical Characteristics				
Driver Rated Wattage	Driver Input Voltage	Drive Current	Driver Output Voltage	Power Factor
100W	100-240V AC	max 4.16A	24V	0.9

Accessories

CCREMOTEB	Handheld remote control	Sold Separately
CCRFCONWIFI	Colour Change RF-WIFI Wall Coverter, 12VDC	Sold Separately
CR575RGBW	5-Core PVC Cable	Sold Separately
LEDRGBWEXT	Colour Change 5-core extension lead for RGBW products	Sold Separately

Guarantee	
Warranty	5 years

Features & benefits

- 4 channel 24V DC Constant Voltage Output
- Multiple control inputs
- Max. 4.16A/CH, CH1+CH2+CH3+CH4=4.16A
- Power repeaters (PR3002) are required for RF installations with multiple zones that want to colour cycle. Requires driver.

