



All-in-one Driver for RGBW/RGB Systems

12 or 24V DC Output

Receives RF signal

CCDRV200RF

200W RF Driver

Features

IP rating	IP20
Dimmable Option	Yes

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-25°C - 40°C
Inrush Current	COLD START Max. 65A at 230VAC
UK Bathroom Zone	1
SELV	SELV
Electric Class (1, 2, 3)	1
Power Factor	0.98

Guarantee

Warranty 5 years

Electrical Characteristics

Driver Rated Wattage	Driver Input Voltage	Drive Current	Driver Output Voltage	Power Factor
200W	100-277V AC	max 8.4A	24V	0.98

Accessories

CCREMOTEB	Handheld remote control	Sold Separately
CCRFCONWIFI	Colour Change RF-WIFI Wall Coverter, 12VDC	Sold Separately
CR575RGBW	5-Core PVC Cable	Sold Separately
LEDRGBWEXT	Colour Change 5-core extension lead for RGBW products	Sold Separately

Features & benefits

- 4 channel 24V DC Constant Voltage Output
- Multiple control inputs
- Max 4.1A/ch, ch1+ch2+ch3+ch4=8.4A
- Power repeaters (PR3002) are required for RF installations with multiple zones that want to colour cycle. Requires driver.

