

All-in-one Driver for  
RGBW/RGB Systems

12 or 24V DC Output

Receives RF signal

## WARRANTY

Warranty

5 years

## FEATURES & BENEFITS

4 channel 24V DC Constant Voltage Output

Multiple control inputs

Max 4.1A/ch, ch1+ch2+ch3+ch4=8.4A

Power repeaters (PR3002) are required for RF installations with multiple zones that want to colour cycle. Requires driver.



# CCDRV200RF

200W RF Driver

## INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-25°C - 40°C
Inrush Current	COLD START Max. 65A at 230VAC
UK Bathroom Zone	1
SELV	Yes
Electric Class (1, 2, 3)	I
Power Factor	0.98

## Electrical Characteristics

Driver Rated Wattage	Driver Input Voltage	Drive Current	Driver Output Voltage	Power Factor
200	100-277V AC	max 8.4A	24	0.98

## ACCESSORIES

CCREMOTEB	Handheld remote control	Sold Separately
CCRFCNVWIFI	Colour Change RF-WIFI Wall Covertor, 12VDC	Sold Separately
CR575RGBW	5-Core PVC Cable	Sold Separately
LEDRGBWEXT	Colour Change 5-core extension lead for RGBW products	Sold Separately