



## CCDRV75RF

75W RF Driver

### Features

IP rating	IP20
Dimmable Option	Yes

### Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-25°C - 40°C
Inrush Current	COLD START Max. 2A @ 230VAC
UK Bathroom Zone	2
SELV	SELV
Electric Class (1, 2, 3)	2
Power Factor	0.9

### Electrical Characteristics

Driver Rated Wattage	Driver Input Voltage	Drive Current	Driver Output Voltage	Power Factor
75W	220-240V AC	300-1500mA	8-43V	0.9

### Accessories

CCREMOTEB	Handheld remote control	Sold Separately
CCRFCONVWIFI	Colour Change RF-WIFI Wall Covertor, 12VDC	Sold Separately
CR575RGBW	5-Core PVC Cable	Sold Separately
LEDRGBWEXT	Colour Change 5-core extension lead for RGBW products	Sold Separately



collingwood

All-in-one Driver for RGBW/RGB Systems

Selectable Voltage by dips (8-43V)

Receives RF signal

### Guarantee

Warranty 5 years

### Features & benefits

- 4 channel output Constant Current (RGBW)
- Multiple control inputs
- Works with 350mA to 1500mA & 8-43V products
- Power repeaters (PR301) are required for RF installations with multiple zones that want to colour cycle. Requires driver.

