

COF STRIP

COF Dotless LED Strip, 8W/m, 5m reel with self adhesive backing

FEATURES

IP rating	IP20
CSP Switchable	Single CCT
Dimmable Option	Driver dependent
LED Lifetime	L90 36,000h
Colour Rendering Index	CRI>90
Colour Consistency	SDCM4
Self-Adhesive Backing	True
Bespoke Lengths	No
Strip type	Dotless flexible tape

INSTALLATION INFORMATION

Input	24V DC
Maximum Ambient Temperature	-20°C - 40°C
Weight	20g/m
Construction Material	Flexible tape
UK Bathroom Zone	N/A
Electric Class (1, 2, 3)	III
Maximum Running Length	2.5 m

PHOTOMETRICS @ 25°C

Product code	w	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
LSFA0727050	8W/m	2700K	140°	680	85	164	A G G
LSFA0730050	8W/m	3000K	140°	690	86	166	A G
LSFA0740050	8W/m	4000K	140°	730	91	176	å G

WIRING INFORMATION

Cable / Flying Lead	Supplied with 500mm, 2x0.5mm² flying lead from one end
Type of Wiring Required	Parallel
Input Cable Type	0.50mm ² RED + BLACK PTFE
Series / Parallel	Parallel

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PS3024B	220-240V	Yes	Yes (with PDCINT 1-10V)	Outside zones	-	3m
PS7524	220-240V	Yes	Yes (with PDCINT 1-10V)	Outside zones	-	9m
PSIPI5024	220-240V	Yes	Yes (with PDCINT 1-10V)	Outside zones	-	18m

ACCESSORIES

LED STRIP PROFILE RANGE	Profile range to house adhesive strip	Sold Separately
PDCINT1-10V	1-10V dimming interface for use with 24V LED drivers	Sold Separately



LIGHTING INNOVATION



Ideal for accent lighting with 8W/m



Ideal for living room and hallways with IP20 rating



Dotless LED strip

WARRANTY

Warranty

3 years

FEATURES & BENEFITS

High quality LED strip maintaining light quality and consistency

Available in 5m reels

CRI 90 providing true colour appearance

Flexible strip to allow installation in a variety of applications and uneven surfaces

Quick and easy installation with 3M selfadhesive backing

Cut points at every 29.4mm

500mm flying leads attached

5m/29.4mm

