
Anti-corrosive specification sheet







Caiman CSP 4ft Twin

CCT Colour Switchable

Features	
IP rating	IP65
IK rating	IK08
CSP Switchable	Switchable CCT
Sensor Option	PIR with accessory
Dimmable Option	No
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4
Emergency Option	Yes, Self-Test

Installation Information				
Input	220-240V AC			
Maximum Ambient Temperature	-20°C - 35°C			
Weight	2Kg (EM: 2.4Kg)			
Inrush Current	30A 0.3ms			
Construction Material	Anti-UV Polycarbonate			
SELV	SELV			
Electric Class (1, 2, 3)	1			

Yes (with modification)

Loop in / Loop out

Part P

Photometrics @ 25°C

Product Code	Finish	Туре	Beam	W	Colour	lm	lm/W	lx@1m	EM lm	Energy
AC4TN Grey RAL7005 Standard					3000K	4140	115	1189	-	
	Standard	120°	36W	4000K	4680	130	1345	-	A D	
				6500K	4500	125	1293	-		

Suitable for coastal areas

Install Connector Type

UK Building Regulations

Wiring Information

•	
Cable Required for Connector	H05RN-F cable diameter 4 - 10mm, max conductor size 3x 1.5mm²
Type of Wiring Required	Parallel

Accessories

AC4TCLIP316	Coastal application kit	Sold Separately
ACTBESA	BESA mounting kit (indoor only)	Sold Separately
EMBOLTMOPEN	3 hour emergency conversion pack, open area, manual test	Sold Separately
EMBOLTMCOR	3 hour emergency conversion pack, corridor area, manual test	Sold Separately
PIRBOLT	PIR on/off daylight Sensor	Sold Separately

collingwood



CCT switchable between 3000K, 4000K & 6500K



Grade 316 Coastal protection kit available



BESA mounting kit available

Guarantee

Warranty 5 years Battery Warranty 2 years On-Site Warranty 2 years

Features & benefits

- IP65 for the highest level of dust protection and able to withstand jets of water from
- 304 stainless steel clips for high corrosion resistance and anti-tamper screws for vandal proofing
- IK08 for robust impact protection
- Unique gear tray slots that allow us to easily integrate third party control gear for your project. Just ask.
- Extended mounting sliders to help make refurbishment easier
- Safety tether cable to gear tray enables fast installation
- Compression cable gland included in fixings kit
- Emergency option available

